

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version Revision Date: SDS Number: Date of last issue: 04-10-2017
6.0 10-07-2021 101214674 Date of first issue: 10-07-2021

BLUE CUBE OPERATIONS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1. IDENTIFICATION

Product name : D.E.H.® 538 Epoxy Curing Agent
Product code : 000000001000000047

Manufacturer or supplier's details

Company name of supplier : BLUE CUBE OPERATIONS LLC
Address : 190 CARONDELET PLAZA, SUITE 1530
 : CLAYTON MO 63105-3467
Telephone : (844) 238-3445
E-mail address : INFO@OLIN.COM
Emergency telephone : +1 800 424 9300
Local Emergency Contact : 1-800-424-9300
Identified uses : Hardener for epoxy resin.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Oral) : Category 4
Skin corrosion : Category 1B
Serious eye damage : Category 1
Skin sensitization : Category 1

GHS label elements

Hazard pictograms :

Signal Word : Danger
Hazard Statements : Harmful if swallowed.
 : Causes severe skin burns and eye damage.

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

May cause an allergic skin reaction.

Precautionary Statements :

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P533 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Benzyl alcohol	100-51-6	>= 30 - <= 60
5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox	68609-08-5	>= 20 - <= 50
3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isopho-	2855-13-2	>= 10 - <= 30

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

ronediamine)		
1,3-Cyclohexanebis(methylamine)	2579-20-6	>= 10 - <= 30
Actual concentration is withheld as a trade secret		

SECTION 4. FIRST AID MEASURES

- If inhaled : Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.
- In case of skin contact : Immediate continued and thorough washing in flowing water for at least 30 minutes is imperative while removing contaminated clothing. Prompt medical consultation is essential. Wash clothing before reuse. Properly dispose of leather items such as shoes, belts, and watchbands. Suitable emergency safety shower facility should be immediately available.
- In case of eye contact : Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.
- If swallowed : Do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Do not give anything by mouth unless the person is fully conscious.
- Most important symptoms and effects, both acute and delayed : Aside from the information found under Description of first aid measures(above)any additional important symptoms and effects are described in Section 11: Toxicology Information.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Maintain adequate ventilation and oxygenation of the patient. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination. Due to irritant properties, swallowing may result in burns/ulceration of mouth, stomach and lower gastrointestinal tract with subsequent stricture. Aspiration of vomitus may cause lung injury. Suggest endotracheal/esophageal control if lavage is done. No specific antidote. Treatment of exposure should be directed at the control of

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

symptoms and the clinical condition of the patient.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water fog or fine spray.
 Dry chemical fire extinguishers.
 Carbon dioxide fire extinguishers.
 Foam.
 Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.
- Unsuitable extinguishing media : Do not use direct water stream.
 May spread fire.
- Specific hazards during fire fighting : Container may rupture from gas generation in a fire situation.
 Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.
- Hazardous combustion products : During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.
 Combustion products may include and are not limited to:
 Nitrogen oxides.
 Carbon monoxide.
 Carbon dioxide.
- Further information : Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.
 Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.
 Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard.
 Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the 'Accidental Release Measures' and the 'Ecological Information' sections of this (M)SDS.
- Special protective equipment for fire-fighters : Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).
 Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version Revision Date: SDS Number: Date of last issue: 04-10-2017
6.0 10-07-2021 101214674 Date of first issue: 10-07-2021

location.
For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate area.
Only trained and properly protected personnel must be involved in clean-up operations.
Keep upwind of spill.
Ventilate area of leak or spill.
Refer to section 7, Handling, for additional precautionary measures.
Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.
- Environmental precautions : Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.
- Methods and materials for containment and cleaning up : Contain spilled material if possible.
Absorb with materials such as:
Sand.
Collect in suitable and properly labeled containers.
See Section 13, Disposal Considerations, for additional information.
-

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not get in eyes, on skin, on clothing.
Avoid breathing vapor.
Do not swallow.
Avoid prolonged or repeated contact with skin.
Keep container closed.
Use with adequate ventilation.
Wash thoroughly after handling.
Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.
See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.
- Conditions for safe storage : Store in a cool, dry place.
Avoid contact with metals such as:
Brass.
Bronze.
Copper.
Copper alloys.
- Recommended storage temperature : 32 - 86 °F / 0 - 30 °C
- Storage period : 12 Months
-

D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
 Date of first issue: 10-07-2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
1,3-Cyclohexanebis(methylamine)	2579-20-6		0.1 ppm 0.8 mg/m ³	OLIN OEL

Engineering measures : Use engineering controls to maintain airborne level below exposure limit requirements or guidelines.
 If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation.
 Local exhaust ventilation may be necessary for some operations.

Personal protective equipment

Respiratory protection : Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines.
 If there are no applicable exposure limit requirements or guidelines, use an approved respirator.
 Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.
 For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Filter type : The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Hand protection

Remarks : Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Natural rubber ('latex'). Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ('EVAL'). Examples of acceptable glove barrier materials include: Butyl rubber. Nitrile/butadiene rubber ('nitrile' or 'NBR'). Polyvinyl alcohol ('PVA'). Polyvinyl chloride ('PVC' or 'vinyl'). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Eye protection : Use chemical goggles.
 If exposure causes eye discomfort, use a full-face respirator.

Skin and body protection : Use protective clothing chemically resistant to this material.
 Selection of specific items such as face shield, boots, apron,

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

or full body suit will depend on the task.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid.
Color	:	Clear
Odor	:	Amine.
Odor Threshold	:	No test data available
pH	:	Not applicable
Melting point/range	:	Not applicable
Freezing point	:	No test data available
Boiling point/boiling range	:	> 392 °F / > 200 °C Method: Literature
Flash point	:	> 212 °F / > 100 °C Method: Literature, closed cup
Evaporation rate	:	No test data available
Flammability (solid, gas)	:	Not applicable to liquids
Flammability (liquids)	:	Not expected to be a static-accumulating flammable liquid.
Self-ignition	:	The substance or mixture is not classified as pyrophoric.
Upper explosion limit / Upper flammability limit	:	No test data available
Lower explosion limit / Lower flammability limit	:	No test data available
Vapor pressure	:	0.2 mbar (68 °F / 20 °C) Method: Literature
Relative vapor density	:	> 1 Method: Literature
Relative density	:	1.0 Method: Literature
Solubility(ies) Water solubility	:	Slightly soluble

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No test data available

Viscosity
Viscosity, dynamic : 250 - 500 mPa,s (77 °F / 25 °C)
Method: ASTM D 445

Viscosity, kinematic : No test data available

Explosive properties : No
Method: Assessment based on structural analysis

Oxidizing properties : No
Method: Assessment based on structural analysis

Note: These are the Reference Points for these Physical Properties listed above, unless otherwise noted in their respective Physical Property value information: Boiling Point at 760 mmHg; Evaporation Rate Butyl Acetate = 1; Relative Vapor Density Air = 1; and Relative Density Water = 1.

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No data available

Chemical stability : Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions : Polymerization will not occur.

Conditions to avoid : Exposure to elevated temperatures can cause product to decompose.
Generation of gas during decomposition can cause pressure in closed systems.
Reaction with carbon dioxide may form an amine carbamate.
Smoke may be generated depending on vapor pressure of mixture.
Product absorbs carbon dioxide from the air.

Incompatible materials : Avoid contact with oxidizing materials.
Avoid contact with:
Acids.
Acrylates.
Alcohols.
Aldehydes.
Halogenated hydrocarbons.
Ketones.
Nitrites.
Avoid contact with metals such as:
Brass.
Bronze.

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

Copper.
Copper alloys.

Hazardous decomposition products : Decomposition products depend upon temperature, air supply and the presence of other materials.
Decomposition products can include and are not limited to:
Aromatic compounds.
Ammonia.
Volatile amines.
Hydrocarbons.
Phenolics.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity**Product:**

Acute oral toxicity : Remarks: Low toxicity if swallowed.
Swallowing may result in gastrointestinal irritation or ulceration.
Swallowing may result in burns of the mouth and throat.

LD50 (Rat): > 1,000 mg/kg
Method: Estimated.
Remarks: Single dose oral LD50 has not been determined.
Based on information for component(s):

Acute dermal toxicity : Remarks: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50 (Rabbit): > 2,000 mg/kg
Method: Estimated.
Remarks: The dermal LD50 has not been determined.
Based on information for component(s):

Components:**Benzyl alcohol:**

Acute oral toxicity : LD50 (Rat, male): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Symptoms: No deaths occurred at this concentration.
Assessment: The substance or mixture has no acute dermal toxicity

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Acute oral toxicity : Remarks: Oral LD50 has not been determined due to corro-

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

sivity.

Acute inhalation toxicity : Remarks: The LC50 has not been determined.

Acute dermal toxicity : Remarks: The dermal LD50 has not been determined.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Acute oral toxicity : LD50 (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.01 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
 Symptoms: No deaths occurred at this concentration.
 Assessment: The substance or mixture has no acute dermal toxicity

1,3-Cyclohexanebis(methylamine):

Acute oral toxicity : LD50 (Rat, female): > 300 - 2,000 mg/kg

Acute inhalation toxicity : Remarks: As product:
 The LC50 has not been determined.

Remarks: Vapor may cause severe irritation of the upper respiratory tract (nose and throat).

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Skin corrosion/irritation**Product:**

Remarks : Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Components:**Benzyl alcohol:**

Remarks : Brief contact is essentially nonirritating to skin.
 Prolonged contact may cause skin irritation with local redness.
 May cause tingling/numbness in exposed areas (paresthesia).

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Result : Causes burns.

Remarks : Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

Result : Causes burns.
 Remarks : Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Remarks : Classified as corrosive to the skin according to DOT guidelines.

1,3-Cyclohexanebis(methylamine):

Result : Causes severe burns.
 Remarks : Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Serious eye damage/eye irritation**Product:**

Remarks : May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.
 Vapor may cause severe eye irritation.
 Vapor may cause lacrimation (tears).

Components:**Benzyl alcohol:**

Remarks : May cause moderate eye irritation.
 May cause corneal injury.
 Effects may be slow to heal.
 Vapor may cause lacrimation (tears).

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Result : Corrosive
 Remarks : May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Result : Corrosive
 Remarks : May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

1,3-Cyclohexanebis(methylamine):

Result : Corrosive
 Remarks : May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.
 Vapor may cause severe eye irritation.
 Vapor of amines may cause swelling of the cornea resulting in visual disturbances such as blurred or hazy vision. Bright lights may appear to be surrounded by halos. Effects may be

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

delayed and typically disappear spontaneously.

Respiratory or skin sensitization**Product:**

Remarks : A component in this mixture has caused allergic skin reactions in humans.
Contains component(s) which have caused allergic skin sensitization in guinea pigs.

Remarks : For respiratory sensitization:
No relevant information found.

Components:**Benzyl alcohol:**

Remarks : For skin sensitization:
No relevant data found.

Remarks : For respiratory sensitization:
No relevant data found.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Assessment : The product is a skin sensitizer, sub-category 1A.
Remarks : Has caused allergic skin reactions when tested in guinea pigs.

Remarks : For respiratory sensitization:
No relevant data found.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Assessment : The product is a skin sensitizer, sub-category 1A.
Remarks : Skin contact may cause an allergic skin reaction.
Has caused allergic skin reactions when tested in guinea pigs.
Has caused allergic skin reactions in humans.

Remarks : For respiratory sensitization:
No relevant data found.

1,3-Cyclohexanebis(methylamine):

Assessment : Does not cause skin sensitization.
Remarks : Did not cause allergic skin reactions when tested in guinea pigs.

Remarks : For respiratory sensitization:
No relevant data found.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: Contains component(s) which were negative in

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

some in vitro genetic toxicity studies and positive in others.
Contains a component(s) which were negative in in vitro genetic toxicity studies.
Contains component(s) which were negative in animal genetic toxicity studies.

Components:**Benzyl alcohol:**

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative in some cases and positive in other cases.
Animal genetic toxicity studies were negative.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative.
Animal genetic toxicity studies were negative.

1,3-Cyclohexanebis(methylamine):

Genotoxicity in vitro : Remarks: In vitro genetic toxicity studies were negative.
Animal genetic toxicity studies were negative.

Carcinogenicity**Product:**

Remarks : Contains component(s) which did not cause cancer in laboratory animals.

Components:**Benzyl alcohol:**

Remarks : Did not cause cancer in laboratory animals.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Remarks : No relevant data found.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Remarks : No relevant data found.

1,3-Cyclohexanebis(methylamine):

Remarks : No relevant data found.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: Contains component(s) which did not interfere with reproduction in animal studies.

Effects on fetal development : Remarks: Contains component(s) which, in laboratory animals, have been toxic to the fetus only at doses toxic to the mother.
Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Components:

Benzyl alcohol:

Effects on fertility : Remarks: No relevant data found.

Effects on fetal development : Remarks: Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Effects on fertility : Remarks: No relevant data found.

Effects on fetal development : Remarks: No relevant data found.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Effects on fertility : Remarks: No relevant data found.

Effects on fetal development : Remarks: Did not cause birth defects in laboratory animals.

1,3-Cyclohexanebis(methylamine):

Effects on fertility : Remarks: In animal studies, did not interfere with reproduction.

Effects on fetal development : Remarks: Did not cause birth defects or any other fetal effects in laboratory animals.

STOT-single exposure

Product:

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

D.E.H.® 538 Epoxy Curing Agent

Version Revision Date: SDS Number: Date of last issue: 04-10-2017
6.0 10-07-2021 101214674 Date of first issue: 10-07-2021

Components:**Benzyl alcohol:**

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

1,3-Cyclohexanebis(methylamine):

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

STOT-repeated exposure**Components:****1,3-Cyclohexanebis(methylamine):**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity**Product:**

Remarks : For the component(s) tested:
In animals, effects have been reported on the following organs:
Central nervous system.
Muscles.
Thymus.
Urinary tract.
Respiratory tract.
Liver.

Components:**Benzyl alcohol:**

Remarks : In animals, effects have been reported on the following organs after inhalation:
Central nervous system.
Muscles.
Thymus.
Urinary tract.
Based on available data, repeated exposures to small amounts are not anticipated to cause significant adverse

D.E.H.® 538 Epoxy Curing Agent

Version Revision Date: SDS Number: Date of last issue: 04-10-2017
6.0 10-07-2021 101214674 Date of first issue: 10-07-2021

effects.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Remarks : In animals, effects have been reported on the following organs:
Liver.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Remarks : In animals, effects have been reported on the following organs:
Respiratory tract.

1,3-Cyclohexanebis(methylamine):

Remarks : Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Aspiration toxicity

Product:

Based on physical properties, not likely to be an aspiration hazard.

Components:

Benzyl alcohol:

Based on physical properties, not likely to be an aspiration hazard.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Based on available information, aspiration hazard could not be determined.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

1,3-Cyclohexanebis(methylamine):

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish : Remarks: Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

the most sensitive species tested).

LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
 Exposure time: 96 h
 Test Type: Static
 Method: Method Not Specified.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
 GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
 End point: Growth rate
 Exposure time: 72 h
 Test Type: Static
 Method: OECD Test Guideline 201
 GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna): 51 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Method: OECD Test Guideline 211
 GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): 2,100 mg/l
 End point: Respiration rates.
 Exposure time: 49 h
 Test Type: Respiration inhibition
 Method: OECD 209 Test

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Toxicity to fish : Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LL50 (Rainbow trout (Oncorhynchus mykiss)): 70.7 mg/l
 Exposure time: 96 h
 Test Type: static test
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (water flea Daphnia magna): 11.1 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 79.4 mg/l
 End point: Growth inhibition (cell density reduction)
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
End point: Respiration rates.
Exposure time: 3 h
Test Type: aerobic
Method: activated sludge test (OECD 209)

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Toxicity to fish : Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50 (Leuciscus idus (Golden orfe)): 110 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203 or Equivalent

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202 or Equivalent

Toxicity to algae/aquatic plants : EbC50 (alga Scenedesmus sp.): 37 mg/l
End point: Biomass
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 3 mg/l
End point: number of offspring
Exposure time: 21 d

Toxicity to microorganisms : EC10 (Bacteria): 1,120 mg/l
Exposure time: 18 h
Test Type: Static

1,3-Cyclohexanebis(methylamine):

Toxicity to fish : Remarks: Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l
Exposure time: 96 h
Method: Method Not Specified.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 29 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 or Equivalent

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 276

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

plants mg/l
 End point: Growth rate inhibition
 Exposure time: 72 h
 Method: OECD Test Guideline 201 or Equivalent

Toxicity to soil dwelling organisms : EC50 (Eisenia fetida (earthworms)): >= 1,000 mg/kg
 Exposure time: 14 d
 End point: growth
 Method: Other guidelines

Persistence and degradability**Components:****Benzyl alcohol:**

Biodegradability : Result: Readily biodegradable.
 Remarks: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Inoculum: activated sludge, domestic (adaptation not specified)

Concentration: 100 mg/l

Biodegradation: 92 - 96 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Remarks: 10-day Window: Not applicable

ThOD : 2.52 mg/mg

Photodegradation : Test Type: Half-life (indirect photolysis)
 Sensitizer: OH radicals
 Rate constant: 8.25E-12 cm³/s
 Method: Estimated.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox:

Biodegradability : Result: Not biodegradable.
 Remarks: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

aerobic

Inoculum: activated sludge

Concentration: 14 mg/l

Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Remarks: 10-day Window: Fail

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Biodegradability : Result: Not biodegradable.
 Remarks: Material is expected to biodegrade very slowly (in

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

the environment). Fails to pass OECD/EEC tests for ready biodegradability.

aerobic

Concentration: 10 mg/l

Biodegradation: 8 %

Exposure time: 28 d

Method: OECD Test Guideline 301A or Equivalent

Remarks: 10-day Window: Fail

aerobic

Concentration: 10.1 mg/l

Biodegradation: 42 %

Exposure time: 3 h

Method: OECD Test Guideline 303A or Equivalent

Remarks: 10-day Window: Not applicable

ThOD : 3.38 mg/mg

Photodegradation : Test Type: Half-life (indirect photolysis)
Sensitizer: OH radicals
Rate constant: 8.472E-11 cm³/s
Method: Estimated.

1,3-Cyclohexanebis(methylamine):

Biodegradability : Remarks: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

Biodegradation: 29 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Remarks: 10-day Window: Fail

Biodegradation: 92 - 96 %

Exposure time: 28 d

Method: OECD Test Guideline 303A or Equivalent

Remarks: 10-day Window: Not applicable

ThOD : 3.37 mg/mg

Bioaccumulative potential**Components:****Benzyl alcohol:**

Partition coefficient: n-octanol/water

: log Pow: 1.10

Method: Measured

Remarks: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

D.E.H.® 538 Epoxy Curing Agent

Version Revision Date: SDS Number: Date of last issue: 04-10-2017
6.0 10-07-2021 101214674 Date of first issue: 10-07-2021

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Partition coefficient: n- : log Pow: 3.6 (77 °F / 25 °C)
octanol/water pH: 7
Remarks: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Partition coefficient: n- : log Pow: 0.79
octanol/water Method: Measured
Remarks: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

1,3-Cyclohexanebis(methylamine):

Partition coefficient: n- : log Pow: 0.44
octanol/water Method: OECD Test Guideline 107 or Equivalent
Remarks: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Mobility in soil**Components:****Benzyl alcohol:**

Distribution among environ- : Koc: 16
mental compartments Method: Estimated.
Remarks: Potential for mobility in soil is very high (Koc between 0 and 50).
Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Distribution among environ- : Koc: > 5000
mental compartments Method: OECD 121: HPLC Method
Remarks: Expected to be relatively immobile in soil (Koc > 5000).

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Distribution among environ- : Koc: 340
mental compartments Method: Estimated.
Remarks: Potential for mobility in soil is medium (Koc between 150 and 500).
Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

1,3-Cyclohexanebis(methylamine):

Distribution among environ- : Koc: > 141 - 832
mental compartments Method: Measured

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

Remarks: Potential for mobility in soil is high (Koc between 50 and 150).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Other adverse effects**Components:****Benzyl alcohol:**

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

5-Amino-1,3,3-trimethylcyclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[ox]:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine):

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

1,3-Cyclohexanebis(methylamine):

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL.
THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information.
All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.
Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.
DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.
FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

SECTION 14. TRANSPORT INFORMATION

International Regulations**UNRTDG**

UN number	:	UN 2735
Proper shipping name	:	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanebis(methylamine), 3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine))
Class	:	8
Packing group	:	II
Labels	:	8

IATA-DGR

UN/ID No.	:	UN 2735
Proper shipping name	:	Amines, liquid, corrosive, n.o.s. (1,3-Cyclohexanebis(methylamine), 3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine))
Class	:	8
Packing group	:	II
Labels	:	Corrosive
Packing instruction (cargo aircraft)	:	855
Packing instruction (passenger aircraft)	:	851

IMDG-Code

UN number	:	UN 2735
Proper shipping name	:	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanebis(methylamine), 3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine))
Class	:	8
Packing group	:	II
Labels	:	8
EmS Code	:	F-A, S-B
Marine pollutant	:	no
Remarks	:	Stowage category AAlkalis

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number	:	UN 2735
Proper shipping name	:	Amines, liquid, corrosive, n.o.s. (1,3-Cyclohexanebis(methylamine), 3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine))
Class	:	8
Packing group	:	II
Labels	:	CORROSIVE
ERG Code	:	153
Marine pollutant	:	no

D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Benzyl alcohol 100-51-6

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

International Regulations

Montreal Protocol : Not applicable
 Rotterdam Convention (Prior Informed Consent) : Not applicable
 Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The ingredients of this product are reported in the following inventories:

CH INV : not determined
 DSL : All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.
 AICS : All intentional components are listed on the inventory, are exempt, or are supplier certified.
 NZIoC : All intentional components are listed on the inventory, are exempt, or are supplier certified.
 ENCS : All intentional components are listed on the inventory, are exempt, or are supplier certified.

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version 6.0 Revision Date: 10-07-2021 SDS Number: 101214674 Date of last issue: 04-10-2017
Date of first issue: 10-07-2021

- ISHL : All intentional components are listed on the inventory, are exempt, or are supplier certified.
- KECI : All intentional components are listed on the inventory, are exempt, or are supplier certified.
- PICCS : All intentional components are listed on the inventory, are exempt, or are supplier certified.
- IECSC : All intentional components are listed on the inventory, are exempt, or are supplier certified.
- TCSI : All intentional components are listed on the inventory, are exempt, or are supplier certified.
- TSCA : All substances listed as active on the TSCA Inventory or are not required to be listed.

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
US WEEL / TWA : 8-hr TWA

SAFETY DATA SHEET



D.E.H.® 538 Epoxy Curing Agent

Version	Revision Date:	SDS Number:	Date of last issue: 04-10-2017
6.0	10-07-2021	101214674	Date of first issue: 10-07-2021

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10-07-2021

BLUE CUBE OPERATIONS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US / Z8