Caspol® 5003 Technical Data Sheet



Product Identification

Caspol® 5003 is a 100% solids castor oil based reactive diluent with a linear chain backbone having a low viscosity, good compatibility and wetting. Caspol® 5003, a linear chain diol, is composed of a blend of primary and secondary hydroxyls which makes this polyol more reactive yielding slightly harder and less flexible components than either Caspol® 5001 or DB Oil.

	<u>Property</u>	<u>Value</u>
Physical	Acid Value	2
Properties	Appearance	Pale liquid
	Color, Gardner	2
	Density, lbs./gal, 25°C	8.03
	Equivalent Weight	214
	Functionality	2
	Hydroxyl Value	262
	Moisture, %	0.02
	Non-Volatile, %	100
	Specific Gravity, 25°C/25°C	0.965
	Viscosity, cP @ 25°C	430
Applications	 Formulation of 100% solids high performance polyurethane coatings 	
	 Low VOC UV resistant 2-component industrial maintenance coatings and thermosetting OEM coatings 	
	 Property improvements such as; flexibility, adhesion, moisture resistance, and chemical resistance in coatings, adhesives, sealants, and elastomeric formulations 	
	 Low VOC force dry and bake topcoats and primers for plastics and metal 	
	 VOC and viscosity reduction in coatings, adhesives and sealants 	
	Urethane Intermediates, Polymers	

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA

USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com

Web: www.vertellus.com