

Plyamul® 303

Version 1.2

Revision Date 12/05/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Plyamul® 303
Product code	:	10000001093

Manufacturer or supplier's details

Company	: H.B. Fuller Company
Address	: 1200 Willow Lake Boulevard Vadnais Heights, MN 55110
Telephone	: 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use	:	Water based adhesive
Restrictions on use	:	For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	white
Odor	sweet

GHS Classification

Carcinogenicity	
ouronrogernony	

: Category 2

GHS label elements

Hazard pictograms



Signal Word

Hazard Statements:

H351 Suspected of causing cancer.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention. **Storage:** P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.



Plyamul®	303
-----------------	-----

Version	12
version	1.2

Revision Date 12/05/2018

Potential Health Effects

Carcinogenicity:		
IARC	Group 2B: Possibly car	cinogenic to humans
	vinyl acetate	108-05-4
OSHA		product present at levels greater than or SHA's list of regulated carcinogens.
NTP	No ingredient of this	product present at levels greater than or tified as a known or anticipated carcinogen

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
vinyl acetate	108-05-4	0.1 - 1

SECTION 4. FIRST AID MEASURES

General advice	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	: Wash off with soap and water.
In case of eye contact	: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
If swallowed	: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: none
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Specific extinguishing	:



	Plyamul® 303
Version 1.2	Revision Date 12/05/2018
methods Further information	: This product is an aqueous mixture that will not burn. Dried product film will burn in a fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8.	
Environmental precautions	: No special environmental precautions required. Prevent product from entering drains.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica ge acid binder, universal binder, sawdust).	I,

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: No special precautions are needed in handling this material
Conditions for safe storage	: Keep container closed when not in use. Keep in a dry, cool place.
Materials to avoid	: Do not freeze. No special restrictions on storage with other products.
Storage temperature	: >= 40 °F

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
vinyl acetate	108-05-4	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 30 mg/m3	OSHA P0
		STEL	20 ppm 60 mg/m3	OSHA P0
		PEL	10 ppm 30 mg/m3	CAL PEL
		STEL	15 ppm 45 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally



Plyamul® 303				
Version 1.2	Revision Date 12/05/2018			
	required. In case of insufficient ventilation, wear suitable respiratory equipment.			
Hand protection Material Remarks	Nitrile rubberFor prolonged or repeated contact use protective gloves.			
Eye protection	: Safety glasses			
Protective measures	: No special protective equipment required.			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold	: liquid : white : sweet : No data available
рН	: 4.5 - 5.5
Melting point/freezing point	: 32 °F
Boiling point/boiling range	: 212 °F
Evaporation rate Flammability (solid, gas)	not determinedNot classified as a flammability hazard
Upper explosion limit	: Upper flammability limit not determined
Lower explosion limit	: Lower flammability limit not determined
Relative vapor density	: not determined
Density Solubility(ies)	: 9.1 - 9.3 lb/gal
Water solubility	: dispersible
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: not determined
Viscosity Viscosity, dynamic Solid Content, % by weight:	: 500 - 1,600 cP : 54.5 - 57

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	:	The product is chemically stable.
Possibility of hazardous	:	Hazardous polymerization does not occur.



SAFETY DATA SHEET

Plyamul® 303		
Version 1.2	Revision Date 12/05/2018	
reactions Hazardous decomposition products	: Stable under normal conditions.	
SECTION 11. TOXICOLOGICAL	INFORMATION	
Acute toxicity		
Components:		
vinyl acetate: Acute oral toxicity	: LD50 Oral Rat: 2,920 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 11.4 mg/l Exposure time: 4 h Test atmosphere: vapor	
Acute dermal toxicity	: LD50 Dermal Rabbit: 2,320 mg/kg	
Skin corrosion/irritation		
No data available		
Serious eye damage/eye irritati	on	
No data available		
Respiratory or skin sensitizatio	n	
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT-single exposure		
No data available		
STOT-repeated exposure		
No data available		
Aspiration toxicity		
No data available		

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity



Plyamul® 303

Version	1.2	

Revision Date 12/05/2018

	Revision Date 12/05/2010
<u>Components:</u> vinyl acetate :	
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 14 mg/l Exposure time: 96 h Test Method: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 52 mg/l Exposure time: 24 h Test Method: static test
Persistence and degradability	
No data available Bioaccumulative potential	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.
---------------------	--

SECTION 14. TRANSPORT INFORMATION

Special precautions for user

Not applicable

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR



Plyamul® 303

Version 1.2

Revision Date 12/05/2018

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	: Carcinogenicity			
SARA 302	: This material does not contain any components with EHS TPQ.	n a section 302		
SARA 313	: The following components are subject to reporting l by SARA Title III, Section 313:	The following components are subject to reporting levels established by SARA Title III, Section 313:		
	vinyl acetate	108-05-4		
Clean Air Act				
The following chemical(s) are 61):	listed as HAP under the U.S. Clean Air Act, Section	on 12 (40 CFR		
vinyl acetate	108-05-4			
US State Regulations				
California Prop 65	Please contact Supplier for more information.			
TSCA DSL REACH AICS NZIOC ENCS KECI PICCS IECSC TWINV Inventories LegendTSCA (L	luct are reported in the following inventories: On TSCA Inventory This product contains one or several componer on the Canadian DSL nor NDSL. Not in compliance with the inventory Not in compliance (Korea), REACH(Europe), AICS (Aust	ralia), NZIoC		



Plyamul® 303


Version 1.2

Revision Date 12/05/2018

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information



The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.