

Product specification

Material Dynasylan® CPTMO
Spec.Code K00

Evonik Resource Efficiency GmbH

Business Line Silanes

www.dynasylan.com or www.protectosil.com

Contact: specification-silanes@evonik.com

Inspection Characteristics	Method	Limits	Units	Z
Colour	ISO 6271	< = 25	mg Pt-Co/l	X
Purity (GC-TCD)	SOP 0806	> = 98.0	%	X
Hydrol. Chloride	SOP 0411	< = 500	mg/kg	X

Report on inspection certificate: X = specific/actual value, C = unspecific value/conformity, T = not reported

Shelf Life (unopened package, appropriate storage conditions): min. 12 months from delivery

This document is computer printed and therefore valid without signature.

All warranty claims in respect of the conformity of our product are subject to our General Terms and Conditions of Sale and Delivery. The data listed above reflects the criteria for our internal quality tests. We do not hereby make any express or implied warranty, whether for specific properties or for fitness for any particular application or purpose. All values are valid for the product when despatched from the works.

The Standard Test Methods can be obtained from specialized publishers. Evonik's test methods are available on request.

Material: Dynasylan® CPTMO		Spec-Code: K00	Page 1 from 1
Print date: 25.11.2015	Valid from: 21.04.1997	Version: 1	