



Date of Preparation: February 7, 2023

Section 1: IDENTIFICATION

Product Name: WANNATE® HT-500

Synonyms: Hexamethylene diisocyanate polymer.

Product Use: Raw material for coatings, adhesives, sealants, or elastomers in

industrial applications.

Restrictions on Use: Not available.

Manufacturer/Supplier: Wanhua Chemical (America) Co., Ltd.

3803 West Chester Pike, Suite 240

Newtown Square, PA 19073

Phone Number: Customer service telephone: 610-566-5297

Telephone in Canada: 833-213-6057

Emergency Phone: North America: Chemtrec 800-424-9300 (domestic)

+1-703-527-3887 (International, collect calls accepted)

Date of Preparation of SDS: February 7, 2023

Section 2: HAZARD(S) IDENTIFICATION

GHS INFORMATION

Classification: Acute Toxicity - Inhalation, Category 4

Sensitization - Respiratory, Category 1

Sensitization - Skin, Category 1

Specific Target Organ Toxicity (Single Exposure), Category 3 - Respiratory

Irritation

LABEL ELEMENTS

Hazard

Pictogram(s):



Signal Word: Danger

Hazard Harmful if inhaled.

Statements: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. May cause respiratory irritation.

Precautionary Statements

Prevention: Avoid breathing mist, vapours, or spray.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves, protective clothing and eye protection.

Wear respiratory protection.

Response: IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention.





Date of Preparation: February 7, 2023

If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

Take off contaminated clothing and wash it before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents and container in accordance with applicable regional,

national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS							
Hazardous Ingredient(s) Hexane, 1,6-diisocyanato-, homopolymer	Common name / Synonyms Not available.	CAS No. 28182-81-2	% wt./wt. ~ 100				
Hexane, 1,6-diisocyanato-	Hexamethylene diisocyanate; HDI	822-06-0	< 0.25				
	Section 4: FIRST-AID MEASURES						

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor.

Acute and delayed symptoms and effects: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergy-prone people who have been sensitized to isocyanates or even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm. Asthma sufferers or people who easily get contact dermatitis should therefore not be exposed to isocyanates. The isocyanate odour does not provide sufficient warning of overexposure due to the high odour thresholds.

Eye Contact:

If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Isocyanates may cause severe watering, formation of solid particles in the eye fluid, glaucoma, photophobia (sensitivity to light), blepharospasm (uncontrollable winking), conjunctivitis (inflammation of the mucous membranes of the eye lids with possible discharge), keratitis (inflammation of the cornea) and damage the cornea (opacity or clouding).

Skin Contact:

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.



WANNATE® HT-500

Date of Preparation: February 7, 2023

Acute and delayed symptoms and effects: May cause an allergic skin reaction. May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Prolonged skin contact may cause redness,

swelling, blistering and possible skin sensitization (dermatitis).

Ingestion: If swallowed: Call a poison center or doctor if you feel unwell. If vomiting

occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person.

Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset,

nausea, vomiting and diarrhea.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Not flammable or combustible by OSHA/WHMIS criteria.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge: This material is sensitive to static discharge at temperatures

at or above the flash point.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO2, water spray or regular foam.

Large Fire: Water spray, fog or alcohol-resistant foam. Move

containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: Oxides of carbon. Oxides of nitrogen. Hydrogen cyanide.

Isocyanate vapours.

Protection of Firefighters: Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only

provide limited protection.

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Keep unauthorized personnel away. Stay upwind. Keep out of low

areas. Ventilate closed spaces before entering. ELIMINATE all

ignition sources (no smoking, flares, sparks or flames in

immediate area).

Personal Precautions: Do not touch or walk through spilled material. Use personal

protection recommended in Section 8.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways.

Methods for Containment: Stop leak if without risk. Do not flush to sewer or allow to enter

waterways.



WANNATE® HT-500

Date of Preparation: February 7, 2023

Methods for Clean-Up: Absorb or cover with dry earth, sand or other non-combustible

material and transfer to containers.

Other Information: See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:

Do not swallow. Avoid breathing mist, vapours, or spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines Component

Hexane, 1,6-diisocyanato-, homopolymer [CAS No. 28182-81-2]

ACGIH: No TLV established. **OSHA:** No PEL established.

Hexamethylene diisocyanate (HDI) [CAS No. 822-06-0]

ACGIH: 0.005 ppm (TWA); (1985)

OSHA: No PEL established.

PEL: Permissible Exposure Limit **TLV:** Threshold Limit Value **TWA:** Time-Weighted Average

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels

of dust, fume, vapour, gas, etc.) below recommended

exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection: Wear safety glasses. Use equipment for eye protection that

meets the standards referenced by CSA Standard CAN/CSA-Z94.3:20 and OSHA regulations in 29 CFR

1910.133 for Personal Protective Equipment.

Hand Protection: Wear protective gloves. Consult manufacturer specifications

for further information.

Skin and Body Protection: Wear protective clothing.

Respiratory Protection: Wear respiratory protection. If engineering controls and

ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved



WANNATE® HT-500

Date of Preparation: February 7, 2023

air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-18, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying

respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to

ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colourless liquid.

Colourless.

Odour: Almost odourless.

Odour Threshold: Not available.

Physical State: Liquid.

pH: Not available.

Melting Point / Freezing

Point:

Not available.

Initial Boiling Point: 285 °C (545 °F)

Boiling Range: Not available.

Flash Point: 203 °C (397.4 °F)

Evaporation Rate: Not available.

Flammability (solid, gas): Not applicable.

Lower Flammability Limit: Not available.

Upper Flammability Limit: Not available.

Vapor Pressure: < 0.00001 hPa at 20 °C (68 °F)

Vapor Density: Not available.

Relative Density: Not available.

Solubilities: Immiscible in water.

Partition Coefficient: n-

Octanol/Water:

Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature:

Not available.

Viscosity: Not available.

Percent Volatile, wt. %: Not available.



WANNATE® HT-500

Date of Preparation: February 7, 2023

VOC content, wt. %: Not available.

Density: Not available.

Coefficient of Water/Oil

Distribution:

Not available.

Section 10: STABILITY AND REACTIVITY

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous

Reactions:

HDI-based isocyanurates may undergo uncontrolled exothermic polymerization upon contact with incompatible materials, especially strong bases, such as triethylamine and sodium hydroxide, trialkyl phosphines, potassium acetate, many metal compounds soluble in organic media or at temperatures over 204°C. The resulting

pressure build-up may rupture closed containers.

Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Incompatible Materials: Acids. Bases. Oxidizers. Water. Amines. Alcohols.

Hazardous Decomposition Products: Not available.

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE

Product Toxicity

Oral: Not available.

Dermal: Not available.

Inhalation: Not available.

Component Toxicity

Component CAS No. LD₅₀ oral LD50 dermal LC₅₀ 18500 mg/m³ Hexane, 1,6-diisocyanato-, 28182-81-2 Not available. Not available. homopolymer (rat); 1H Hexamethylene diisocyanate 822-06-0 350 mg/kg 570 uL/kg 30 mg/m³ (mouse) (rabbit) (mouse);

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs.

Symptoms (including delayed and immediate effects)

Inhalation: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties

if inhaled. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergy-prone people who have been sensitized to isocyanates or even have not

been previously exposed to isocyanates may experience symptoms at

concentrations as low as 0.0014 ppm. Asthma sufferers or people who easily get contact dermatitis should therefore not be exposed to isocyanates. The isocyanate



WANNATE® HT-500

Date of Preparation: February 7, 2023

odour does not provide sufficient warning of overexposure due to the high odour

thresholds.

Eye: May cause eye irritation. Signs/symptoms may include redness, swelling, pain,

tearing, and blurred or hazy vision. Isocyanates may cause severe watering, formation of solid particles in the eye fluid, glaucoma, photophobia (sensitivity to light), blepharospasm (uncontrollable winking), conjunctivitis (inflammation of the mucous membranes of the eye lids with possible discharge), keratitis (inflammation

of the cornea) and damage the cornea (opacity or clouding). I

Skin: May cause an allergic skin reaction. May cause skin irritation. Signs/symptoms may

include localized redness, swelling, and itching. Prolonged skin contact may cause

redness, swelling, blistering and possible skin sensitization (dermatitis).

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain,

stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Allergy-prone people who have been sensitized to isocyanates or

even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm.

Respiratory Sensitization: Allergy-prone people who have been sensitized to isocyanates or

even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm.

Medical Conditions

Aggravated By Exposure:

Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity: This product does not contain any carcinogens or potential

carcinogens above reportable thresholds as listed by ACGIH, IARC,

OSHA, or NTP.

Mutagenicity: Not available.

Reproductive Effects: Not available.

Developmental Effects

Teratogenicity: Not available. Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Other Adverse Effects: Not available.





Date of Preparation: February 7, 2023

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national

and local laws and regulations. Local regulations may be more

stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Proper Shipping Name:

Class:

Not applicable.

UN Number:

Packing Group:

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name:

Class:

Not regulated.

Not applicable.

Not applicable.

Packing Group:

Not applicable.

Not applicable.

Not applicable.

Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

Component	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313	RCRA CODE	CAA 112(r) TQ (lbs.)
Hexamethylene diisocyanate	Not listed.	Not listed.	100	313#	Not listed.	Not listed.



WANNATE® HT-500

Date of Preparation: February 7, 2023

SAFETY DATA SHEET State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of

Massachusetts Regulations Section 670.000)

ComponentCAS No.RTK ListHexamethylene diisocyanate822-06-0Listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated

Section 34:5A-5)

ComponentCAS No.RTK ListHexamethylene diisocyanate822-06-0Listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component

CAS No.

RTK List

Hexamethylene diisocyanate

822-06-0

Listed.

California

California Prop 65: This product does not contain chemicals known to the State of California

to cause cancer, birth defects or other reproductive harm.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: February 7, 2023

Version: 1.0

GHS SDS Prepared by: Aegis Regulatory Inc.

Phone: 1 (519) 488-0351

www.aegisreg.com