





## TECHNICAL DATA SHEET

## Orgasol® 2001 EXD NAT 1



**MFTHOD** 

ISO 1068 ISO 11357-3



## MAIN APPLICATIONS

Wood coating, plastic coating, rubber coating and flooring

ORGASOL® 2001 EXD NAT 1 is a spheroïdal powder of polyamide 12, with 10 µm as average diameter and a narrow particle size distribution. An extremely high level of quality is achieved thanks to our rigorous control of particle size distribution, providing excellent consistency in performance.

ORGASOL® 2001 EXD NAT 1 is used as additive in coatings to provide scratch and abrasion resistance and to adjust gloss level.

The best performances are obtained in coatings with low thickness (below approx. 20 µm). The high chemical resistance of polyamide 12 and the particle size distribution are among the key parameters that make ORGASOL® 2001 EXD NAT 1 compatible with most resins and common formulating additives used in coating industry. It can be added to interior or exterior paints and easily dispersed in solvent or water based or 100% solid UV curable systems.

<u> </u>		
Appearance:	White spheroïdal powder	Visual
Average diameter:	10 microns	ISO 13319
Particle size distribution:		
Fine particles < 5 microns	2 max. %	ISO 13319
Coarse particles > 20 microns	2 max. %	ISO 13319
Average Specific Surface Area:	4 m²/g	ISO 9277
Apparent density unpacked:	0.275 g/cm <sup>3</sup>	ISO 1068

177

## **PACKAGING**

15 Kg multilayers bags

**Melting point:** 

**CHARACTERISTICS** 

The information contained in this document is based on trials carried out by our Research Centres and date selected from the literature, but shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment from our part. Our formal specifications define the limit of our commitment.

No liability whatsoever can be accepted by Arkema with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.



420, rue d'Estienne d'Orves 92700 Colombes - France Tél.: 33 (0)1 49 00 80 80 Fax: 33 (0)1 49 00 83 96 www.arkema.com