

Technical Bulletin**TERMIX[®] 5270 Surfactant****PRODUCT DESCRIPTION**

TERMIX[®] 5270 surfactant is a tank mix adjuvant designed to promote activity in the spray tank as a wetting and compatibility agent.

APPLICATION

- Compatibility agent
- Wetting agent
- Compatibility agent for drift control agents

SALES SPECIFICATIONS**Property**

Appearance, 25°C

Specifications

Clear to slightly hazy liquid

Test Method*

ST-30.1

*Methods of Test are available from Huntsman Corporation upon request.

ADDITIONAL INFORMATION**Regulatory Information**

Please see MSDS for inventory status and other regulatory information.

Typical Properties

Density, g/mL, 20°C (68°F)	1.1
Flash point, PMCC, °C/°F	70/158
Viscosity, kinematic, cSt, 25°C (77°F)	925
Viscosity, kinematic, cSt, 40°C (104°F)	400
Weight, lbs/US gal, 25°C (77°F)	9.19

TOXICITY AND SAFETY

For information on the toxicity and safe handling of this product, please read the Material Safety Data Sheet prior to use of the product.

HANDLING AND STORAGE

TERMIX[®] 5270 surfactant may be satisfactorily stored in stainless steel tanks using steel pipes and pumps.

For longer term color stability, it is recommended that the product be stored under an inert atmosphere.

Low pressure steam coils in storage tanks and steam tracing of transfer lines should be provided in cases where low environmental temperatures may make pumping of the product difficult.

SHIPPING DATA

Product is available in tank cars or tank trucks. Small samples are available by contacting our sample department at 1-800-662-0924.

**Huntsman Corporation
Business Offices**

10003 Woodloch Forest Dr.
The Woodlands, TX 77380
(281) 719-6000

**Huntsman Advanced Technology
Center**

Technical Service
8600 Gosling Rd.
The Woodlands, TX 77381
(281) 719-7780

Samples 1-800-662-0924

www.huntsman.com

3902-0214

Copyright © 2010, 2014 Huntsman Corporation or an affiliate thereof. All rights reserved.

TERMIX is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Huntsman Petrochemical Corporation warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. Liability of Huntsman Petrochemical Corporation and its affiliates for all claims is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, user should obtain detailed information on toxicity, together with proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards.