

DESCRIPTION

TEGO® Dispers 652 is a wetting and dispersing additive for inorganic pigments. Can be used in direct grinds of solventborne and radiation-curing formulations to reduce the viscosity. As a co-additive in universal colorants, it acts as a compatibilizer.

KEY BENEFITS

- effective stabilization of inorganic pigments
- universal stability
- solvent-free, 100% active and liquid

EFFECT**Viscosity reduction with organic pigments/carbon blacks****Color intensity/gloss with organic pigments/carbon blacks****Viscosity reduction with inorganic pigments/fillers****Color intensity/gloss with inorganic pigments/fillers****SUITABILITY**

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
direct grind	resin-containing pigment concentrates
●	●
resin-free pigment concentrates	universal pastes
●	●

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- General industrial coatings
- Architectural paints
- Wood coatings
- Pigment concentrates

TECHNICAL DATA

acid value (as supplied)	Approx 35 mg KOH/g
active matter content	100 %
amine value (as supplied)	Approx 20 mg KOH/g
appearance	clear to slightly hazy liquid (product properties are not affected by haziness)
chemical description	concentrate of a fatty acid derivative

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Butylacetate
●	●
Mineral Spirits	
●	

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on inorganic pigment: 0.3 - 2.0 %
As supplied calculated on total formulation: 0.5 - 2.5 %

PROCESSING INSTRUCTIONS

- Add to the grind before dispersion.
- Haziness caused by low temperatures can be eliminated by warming the product. This does not affect the performance properties of the product.

HANDLING & STORAGE

When stored in an original unopened packaging between -40 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture. Eventually, the product may exhibit inhomogenities. Before use it should be homogenized by heating up to 40 °C and processed in the homogeneous state.

MSDS & REGULATORY INFORMATION

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Resource Efficiency GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com