

Technical Bulletin**SURFONIC[®] L24-7 Surfactant****PRODUCT DESCRIPTION**

SURFONIC[®] L24-7 surfactant is the seven-mole ethoxylate of linear, primary 12-14 carbon number alcohol. It is a water-soluble, nonionic surface active agent which is compatible with other nonionic surfactants and with most anionic and cationic surfactants. The product is a clear to slightly turbid liquid.

APPLICATIONS

- Detergents
- Laundry Prespotters
- Hard Surface Cleaners
- Personal Care Products
- Emulsifiers
- Adjuvants for Agricultural Herbicides and Insecticides

SALES SPECIFICATIONS

<u>Property</u>	<u>Specifications</u>	<u>Test Method*</u>
Appearance at 30°C	Clear to slightly turbid, substantially free of foreign matter	ST-30.1
Cloud point, °C (1% Aqueous)	49 - 53	ST-9.1, 5.2.1
Color, Pt-Co	50 max.	ST-30.12
pH, 1% in 10:6 IPA:H ₂ O	6.5 - 8.0	ST-31.36, F
Water, wt%	0.2 max.	ST-31.53

*Methods of Test are available from Huntsman Corporation upon request.

ADDITIONAL INFORMATION**Chemical Properties**

Molecular Weight (theoretical)	487
EO Content, wt% (theoretical)	59.1
HLB Value	11.9
Water Solubility	Soluble
Hydroxyl Number (theoretical)	117

Regulatory Information

CAS Number 68551-12-2
See SDS for all regulatory information.

Shelf Life

The product should retain its conformance to sales specifications for a period of at least two years from date of manufacture if the product is stored at less than 100°F in its undamaged, unopened, factory packaged container.

In general, the user should determine the suitability of any chemical compound, no matter what the shelf life or length of time of storage. Each user should conduct a sufficient investigation to establish the suitability of any product for his intended use.

Typical Properties

Flash point, PMCC, °F	375
Flash point, PMCC, °C	190
Pour point, °F	60
Pour point, °C	16
Density, g/ml, 25°C (77°F)	0.9824
Weight, lbs/US gal, 25°C (77°F)	8.17
Viscosity, kinematic	
cSt, 25°C (77°F)	48
cSt, 37.8°C (100°F)	33
Vapor Pressure, Torr, 25°C	<1x10 ⁻⁵
Critical Micelle Concentration, ppm, 25°C	16
Surface Tension, dynes/cm, 25°C	
0.10% solution	28

TOXICITY AND SAFETY

For information on the toxicity and safe handling of this product, read the Safety Data Sheet prior to use of the product.

HANDLING AND STORAGE

SURFONIC® L24-7 surfactant may be satisfactorily stored in carbon steel tanks using steel pipes and pumps. Caution must be exercised, however, to keep the material in the anhydrous state to prevent severe corrosion to the carbon steel tank and related equipment. A drier on the breathing nozzle is recommended to help maintain anhydrous conditions in the storage tank.

For longer term color stability, it is recommended that the product be stored under an inert atmosphere. Solid sediment may form upon standing. There should be circulation in the storage vessel to keep solids suspended.

Low pressure steam coils in storage tanks and steam tracing of transfer lines should be provided in cases where low environmental temperatures may make pumping of the product difficult.

SHIPPING DATA

Product is available in tank cars, tank trucks and drums of 430 pounds (195 kilograms) net weight. Small samples are available by contacting any Huntsman Performance Products sales office.

BIODEGRADABILITY AND ENVIRONMENTAL SAFETY

Linear alcohol ethoxylates, including the SURFONIC® L series surfactants, undergo rapid and extensive biodegradation under both laboratory and environmental conditions. Their mineralization to CO₂ and water (ultimate biodegradation) is essentially complete during biological wastewater treatments at warm to cold water temperatures. They are degraded by bacteria in rivers, lakes, groundwater and sediment as well.

The major mechanism of biodegradation is cleavage of the ethoxylate chain from the alkyl group with oxidation of the latter to fatty acid. The fatty acid degrades more rapidly than the ethoxylate chain, which is broken down by sequential oxidation and removal of ethoxylate units.

Alcohol ethoxylates begin to lose their toxicity toward aquatic organisms as soon as biodegradation begins. Water containing degraded surfactant has been shown not to adversely affect fish, invertebrates and algae. Thus, while alcohol ethoxylates are toxic to aquatic organisms, in the event of a spill into a waterway any acute effects would be limited in area and time.

SURFONIC® L-series surfactants and other linear alcohol ethoxylates pose no serious threat to the environment. They do not accumulate in any environmental compartment and are found, if at all, only at concentrations below chronic effects levels.

Cleaning products containing SURFONIC® L-series surfactants may be disposed of safely by flushing down the drain with water.

General References

1. Swisher, R. D., Surfactant Biodegradation, Marcel Dekker, 1987.
2. Talmage, S. S., Environmental and Human Safety of Major Surfactants: Alcohol Ethoxylates and Alkylphenol Ethoxylates, a report to the Soap and Detergent Association, Lewis Publishers, 1994.

**Huntsman Corporation
Business Offices**
10003 Woodloch Forest Dr.
The Woodlands, TX 77380
(281) 719-6000

**Huntsman Advanced Technology
Center**
Technical Service
8600 Gosling Rd.
The Woodlands, TX 77381
(281) 719-7780

www.huntsman.com

Copyright © 2007, 2009, 2017 Huntsman Corporation or an affiliate thereof. All rights reserved.

SURFONIC® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Huntsman Corporation warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, HUNTSMAN MAKES NO WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT OF ANY THIRD PARTY, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND ANY USER OF PRODUCTS DESCRIBED HEREIN SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE AND ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. Products may be toxic and require special precautions in handling. For all products described herein, the user should obtain detailed information on toxicity, together with proper shipping, handling, and storage procedures, and should comply with all applicable safety and environmental standards. The behavior, hazards and/or toxicity of the products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which may not be known to Huntsman. It is the sole responsibility of the user of such products to evaluate the manufacturing circumstances and the final products under actual end-use requirements and to adequately advise and warn future purchasers and users thereof.

3014-0417