ALKOSYNT® IT 60



DESCRIPTION

ALKOSYNT® IT 60 is a polyoxyethylene (6) isotridecyl alcohol ether

PHYSICAL PROPERTIES¹

Appearance (25°C) Clear/Hazy Liquid
Active Content, wt% 100%

Moles of EO 6

Hydroxyl Number 121 mgKOH/g

Cloud Point* 70°C HLB 11.4 Flash Point (Open cup) 175°C **Pour Point** 12°C pH (1 wt% aqueous, 25°C) 6.5 Viscosity (25°C) 52 mPa.s Density (20°C) 0.980 g/mL Color (Pt-Co, 25°C) 80 (max) Water Content ≤ 0.2 wt.%

Solubility Water soluble at 25°C

Contact Angle (on Parafilm, 0.5 wt%) 35° (25°C)

Equilibrium Surface Tension 27 mN/m (0.5 wt%, 20°C)

Acid Value ≤ 0.5 mgKOH/g

CHARACTERISTICS AND BENEFITS

- •Versatile surfactant for oil in water emulsification
- •Water soluble, alternative to nonylphenol ethoxylates
- •Excellent, low foaming degreaser
- Nonionic biodegradable surfactant that does not precipitate in the presence of hard water ions.

STORAGE AND HANDLING

Store in a covered, well-ventilated area, away from sunlight and away from sources of heat or open flame. Ensure that the storage locale has adequate control of temperature, pressure, and humidity. Keep the containers hermetically sealed when not in use. For more information, consult the Safety Data Sheet (SDS).

78330-21-9

SHELF LIFE

24 Months from manufacturing date

STANDARD PACKAGING

Drums (441 lbs, 200 kg) Bulk

Totes (metric ton)

REGULATORY CAS Registry No.²

USA (TSCA) Listed Canada (DSL) Listed Australia (AICS) Listed China (IECSC) Listed Korea (ECL) Listed Listed New Zealand (NZIoC) Philippines (PICCS) Listed EU (EINECS) Not listed EU (ELINCS) Not Listed **US DOT** Classified **US EPA Inert Ingredient** 40 CFR 180.910 **US EPA Inert Ingredient** 40 CFR 180.930 **UP EPA Inert Ingredient** 40 CFR 180.940(a)

ADDITIONAL INFORMATION

Sourcing Synthetic Percent Renewable Content 0%

INCI Name Not applicable

US Production Yes

¹The physical properties described in the table are only for informational purposes and may be changed without notice. Please contact Oxiteno for updated data. ²Chemical Abstracts Service.A1668

DISCLAIMER

This information is given in good faith, based on Oxiteno's current knowledge on the subject, and is purely indicative. Any information, including suggestions for using the products, should not preclude experimental testing and verification, which are essential to ensure the suitability of the products to each specific application. All users shall also abide by local laws and obtain all necessary permits. When handling the product, consult the safety data sheet. In case of questions or additional needs, please contact Oxiteno through our customer service channels.

COMMERCIAL OFFICES

Brazil	Colombia	Argentina	Mexico	United States
+55 11 3177 6102	+57 11 555 0070	+54 11 4115 5600	+52 55 5322 0560	+1 346 718 6200
oxiteno@oxiteno.com	oxiteno.colombia@oxiteno.com	oxiteno.argentina@oxiteno.com	oxiteno.mexico@oxiteno.com	oxiteno.usa@oxiteno.com

^{*10} wt% in a 25% BDG aqueous solution