

RILSAN® BESNO P40

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Arkema Inc. 900 First Avenue King of Prussia, Pennsylvania 19406

Specialty Polyamides

Customer Service Telephone Number:	(800) 932-0420
	(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation:

Medical:

CHEMTREC: (800) 424-9300 (24 hrs., 7 days a week) Rocky Mountain Poison Center: (866) 767-5089 (24 hrs., 7 days a week)

Product Information

Product name: Synonyms: Molecular formula: Chemical family: Product use: RILSAN® BESNO P40 Not available (C11H23NO2)x polyamide Mouldings and Extrusion

2. HAZARDS IDENTIFICATION

Emergency Overview

Color:	black
Physical state:	solid
Form:	pellets
Odor:	odourless

*Classification of the substance or mixture:

Not a hazardous substance or mixture.

GHS-Labelling

Supplemental Hazard Statements:

Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

Supplemental information:

Potential Health Effects:

The product, in the form supplied, is not anticipated to produce significant adverse human health effects. Contains high molecular weight polymer(s). Effects due to processing releases: Irritating to eyes, respiratory system and skin.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 1 / 11



RILSAN® BESNO P40

Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure).

Other:

Handle in accordance with good industrial hygiene and safety practice. (pellets/granules) This product may release fume and/or vapor of variable composition depending on processing time and temperature.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Undecanoic acid, 11-amino-, homopolymer	25587-80-8	> 88 %	Not classified
Benzenesulfonamide, N-butyl-	3622-84-2	< 12 %	H412

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of immediate medical attention and special treatment needed, if necessary:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 2 / 11



RILSAN® BESNO P40

5. FIREFIGHTING MEASURES

Extinguishing media (suitable):

Water spray, Carbon dioxide (CO2), Foam

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

When burned, the following hazardous products of combustion can occur: Carbon oxides Hazardous organic compounds Hydrogen cyanide (hydrocyanic acid) (traces) Sulphur compounds

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:

Prevent further leakage or spillage if you can do so without risk. Ventilate the area. Sweep up and shovel into suitable properly labeled containers for prompt disposal. Possible fall hazard – floor may become slippery from leakage/spillage of product. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

7. HANDLING AND STORAGE

Handling

General information on handling:

Avoid breathing dust.

Avoid breathing processing fumes or vapors. Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

Storage

General information on storage conditions:

Keep in a dry, cool place. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Store away from moisture and heat to maintain the technical properties of the product.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 3 / 11



RILSAN® BESNO P40

Storage stability – Remarks: Stable under normal conditions.

Storage incompatibility – General: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Particles Not Otherwise Specified / Nuisance Dust (Proprietary)

US. ACGIH Threshold Limit Values

Form:	Inhalable particles.
Time weighted average	10 mg/m3
Form:	Respirable particles.
Time weighted average	3 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form: PEL: Respirable fraction. 5 mg/m3

Form: PEL: Total dust 15 mg/m3

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Respirable fraction.
Time weighted average	15millions of particles per cubic foot of air
Form:	Total dust
Time weighted average	50millions of particles per cubic foot of air
Form:	Respirable fraction.
Time weighted average	5 mg/m3
Form:	Total dust
Time weighted average	15 mg/m3

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 4 / 11



RILSAN® BESNO P40

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Respiratory protection:

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

Eye protection:

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

9. PHYSICAL AND CHEMICAL PROPERTIES		
Color:	black	
Physical state:	solid	
Form:	pellets	
Odor:	odourless	
Odor threshold:	No data available	
Flash point	No data available	
Auto-ignition temperature:	No data available	
Lower flammable limit (LFL):	Not applicable	
Upper flammable limit (UFL):	Not applicable	

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 5 / 11



RILSAN® BESNO P40

pH:	No data available
Density:	No data available
Specific Gravity (Relative density):	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Boiling point/boiling range:	No data available
Melting point/range:	347 - 374 °F (175 - 190 °C)
Freezing point:	No data available
Evaporation rate:	No data available
Solubility in water:	negligible
Viscosity, dynamic:	No data available
Oil/water partition coefficient:	No data available
Thermal decomposition	> 662 °F (350 °C)
Flammability:	See GHS Classification in Section 2

10. STABILITY AND REACTIVITY

Stability:

The product is stable under normal handling and storage conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

None known.

Conditions / hazards to avoid:

Store protected from moisture and heat. (to maintain the technical properties of the product). See Hazardous Decomposition Products below.

Hazardous decomposition products:

Thermal decomposition giving toxic, flammable, and / or corrosive products: Carbon oxides Ammonia Hydrogen cyanide (hydrocyanic acid) (traces) Hazardous organic compounds

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 6 / 11



RILSAN® BESNO P40

Amine derivatives Sulphur compounds

11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Oral:

Acute toxicity estimate > 5,000 mg/kg.

Data for Undecanoic acid, 11-amino-, homopolymer (25587-80-8)

Acute toxicity

Oral: No deaths occurred. (Rat) LD0 > 2,000 mg/kg.

Dermal: No deaths occurred. (Rat) LD0 > 2,000 mg/kg.

Skin Irritation: Not irritating. (In vitro)

Eye Irritation: Not corrosive (Bovine cornea)

Skin Sensitization: Not a sensitizer. LLNA: Local Lymph Node Assay. (Mouse) No effect is reported.

Repeated dose toxicity

Subchronic dietary administration to rat, dog / No adverse systemic effects reported.

Genotoxicity

Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria

Other information

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance.

Data for Benzenesulfonamide, N-butyl- (3622-84-2)

Acute toxicity

Oral: May be harmful if swallowed. (rat) LD50 = 2,070 mg/kg.

Dermal:

No deaths occurred. (rat) LD0 > 2,000 mg/kg.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 7 / 11

Quick-FDS [18789-47829-06061-018193] - 2019-06-10 - 13:17:10



RILSAN® BESNO P40

Inhalation:

No deaths occurred. (rat) 4 h LC0 > 4.1 mg/l. (aerosol)

Skin Irritation: Not irritating. (rabbit) Irritation Index: 0 / 8. (4 h)

Eye Irritation:

Not irritating. (rabbit) Irritation Index: 0 / 110.

Skin Sensitization:

Not a sensitizer. LLNA: Local Lymph Node Assay. (mouse) No effect is reported.

Repeated dose toxicity

Repeated oral administration to rat / affected organ(s): Thymus, liver / signs: changes in organ structure or function / (Repeated exposure at high concentrations)

Repeated oral administration to rat / affected organ(s): kidney / signs: hyaline droplet nephropathy / (not considered relevant in humans)

Repeated dermal administration to rat / No adverse systemic effects reported.

Genotoxicity

Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, human cells, animal cells

Developmental toxicity

Exposure during pregnancy. oral (rat) / No birth defects were observed.

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (Rat) / Testicular toxicity At high dose : decreased fertility / (toxic effects also observed in the parental animals at these doses)

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

Data for Benzenesulfonamide, N-butyl- (3622-84-2)

Biodegradation:

Not readily biodegradable. (28 d) biodegradation 18 %

Octanol Water Partition Coefficient:

log Pow = 2.01 (measured)

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for Benzenesulfonamide, N-butyl- (3622-84-2)

Aquatic toxicity data:

Harmful. Danio rerio (zebra fish) 96 h LC50 = 36.7 mg/l

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 8 / 11



RILSAN® BESNO P40

Aquatic invertebrates:

Harmful. Daphnia magna (Water flea) 48 h EC50 = 56 mg/l

Algae:

Harmful. Selenastrum capricornutum (green algae) 72 h EC50 = 83 mg/l

Microorganisms:

Practically nontoxic. Activated sludge 3 h EC50 > 6,000 mg/l

13. DISPOSAL CONSIDERATIONS

Waste disposal:

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

14. TRANSPORT INFORMATION

US Department of Transportation (DOT): not regulated

International Maritime Dangerous Goods Code (IMDG): not regulated

15. REGULATORY INFORMATION			
Chemical Inventory Status			
EU. EINECS	EINECS	Conforms to	
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.	
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL	
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to	
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Conforms to	
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Conforms to	
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to	

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 9 / 11



RILSAN® BESNO P40

Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

No SARA Hazards

SARA Title III - Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

United States - State Regulations

New Jersey Right to Know

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

Chemical name	CAS-No.
Undecanoic acid, 11-amino-, homopolymer	25587-80-8

Benzenesulfonamide, N-butyl-

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H412 Harmful to aquatic life with long lasting effects.

Latest Revision(s):

Product code: A61160

Version 1.2

Issued on: 11/10/2016

3622-84-2

Page: 10 / 11



RILSAN® BESNO P40

Reference number:	00000035289
Date of Revision:	11/10/2016
Date Printed:	11/16/2016

RILSAN® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (http://www.arkema.com/en/social-responsibility/responsible-product-management/medicaldevice-policy/index.html) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.

Product code: A61160

Version 1.2

Issued on: 11/10/2016

Page: 11 / 11

Quick-FDS [18789-47829-06061-018193] - 2019-06-10 - 13:17:10