Dynasylan® PTEO





1. Identification

1.1. Product identifier

Trade name Dynasylan® PTEO
Chemical Name Triethoxypropylsilane

CAS-No. 2550-02-9

1.2. Recommended use of the chemical and restrictions on use

Relevant applications identified For industrial use Function Surface modifier Raw material

1.3. Details of the supplier of the safety data sheet

Company Evonik Corporation USA

299 Jefferson Road

Parsippany, NJ 07054-0677

USA

Telephone 973-929-8000

Telefax 973-929-8040

Email address Product-Regulatory-Services@Evonik.com

1.4. 24 HOUR EMERGENCY TELEPHONE NUMBERS:

CHEMTREC - US &

800-424-9300

CANADA:

CHEMTREC MEXICO: 01-800-681-9531

CHEMTREC +1 703-527-3887 (collect calls accepted)

INTERNATIONAL:

Product Regulatory : 973-929-8060

Services

2. Hazards identification

2.1. Classification of the substance or mixture

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Flammable liquids Category 3 H226
Skin irritation Category 2 H315
Acute aquatic toxicity Category 3 H402
Chronic aquatic toxicity Category 3 H412

2.2. Label elements

Statutory basis Globally Harmonized System of Classification and Labelling of Chemicals

(GHS)

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 2 / 14



Symbol(s)





Signal word Warning

Hazard statement H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statement:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Prevention P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash skin thoroughly after handling. P273 - Avoid release to the environment.

P280 - Wear protective gloves/ eye protection/ face protection.

Precautionary statement:

Reaction

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P332 + P313 - If skin irritation occurs: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

Precautionary statement:

Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

Precautionary statement:

Dispos al

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other hazards

None known

3. Composition/information on ingredients

Triethoxypropylsilane

CAS-No. 2550-02-9
Flammable liquids
Skin irritation
Acute aquatic toxicity

Category 3 Category 2

Category 2

Category 3

Other information

This material is classified as hazardous under OSHA regulations.

4. First aid measures

4.1. Description of first aid measures

General advice

Remove contaminated or saturated clothing immediately and dispose of safely.

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 3 / 14



Inhalation

If aerosol or mists are inhaled, take affected persons out into the fresh air. Possible discomforts include severe irritation of mucus lining (nose, throat, eyes), cough, sneezing and flow of tears. In case of persistent discomfort, obtain medical attention immediately.

Skin contact

Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Obtain medical attention immediately if symptoms occur. Wash clothing before reuse.

Eye contact

In case of contact, immediately flush eyes with plenty of water, or if necessary, with eye rinsing solution. In case of persistent discomfort, consult an ophthalmologist.

Ingestion

If accidentally swallowed, rinse mouth thoroughly with water and afterwards, drink plenty of water. In case of discomfort, obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms 5

None known

4.3. Indication of any immediate medical attention and special treatment needed

If required, therapy of irritative effect.

After absorbing large amounts of substance:

administration of activated charcoal.

Acceleration of gastrointestinal passage

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Use water spray or fog, foam, dry chemical or CO2.

5.2. Special hazards arising from the substance or mixture

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Closed container may rupture if strongly heated.

In case of fire cool endangered containers with water.

5.3. Advice for firefighters

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

6.2. Environmental precautions

Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

6.3. Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Additional advice

Remove sources of ignition and ventilate area.

Run off may create fire or explosion hazard in sewer.

Dynasylan® PTEO





Assure sufficient ventilation.

7. Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment; see section 8. Vapors may spread long distances and travel to areas away from the work site before igniting or flashing back to the vapor source.

Keep away from heat, sparks, flames and other sources of ignition. Keep container tightly closed. Use only with adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

This material may have a low electrical conductivity and therefore may accumulate dangerous levels of static electricity. An ignitable vapor-air mixture can form inside storage tanks.

The user must be sure to dissipate static charge by careful bonding and grounding of all equipment and personnel involved in fluid transfer with continuity checks to prove effectiveness. Additional precautions against fire and explosion are the use of inert gas to purge vapor space; dip-pipes while filling vessels, especially lined vessels; grounded tank level floats; reduced flow velocity; self-closing valves on transfer lines and flame arrestors in vent lines.

Additional guidance on fire and explosion protection may be found in various consensus standards, including NFPA 30, 69 and 77 and API 2003 as well as OSHA regulation 29CFR1910.106.

Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

Storage

Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture.

Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

8. Exposure controls/personal protection

8.1. Control parameters

Other information

No substance-specific limiting value being known.

8.2. Exposure controls

Engineering measures

Use this product preferably in a closed system, or use process enclosures, local exhaust ventilation or other engineering controls to minimize airborne exposure.

Personal protective equipment

Respiratory protection

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Glove material for example, butyl-rubber

Material thickness 0.5 mm

Break through time >= 480 min

Glove material for example, Fluorinated rubber (Viton)

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 5 / 14



Material thickness 0.4 mm

Break through time >= 480 min

Selection of protective gloves to meet the requirements of specific workplaces.

Suitability for specific workplaces should be clarified with protective glove manufacturers.

The information is based on our own tests, references from the literature and information from glove manufacturers, or derived by analogy with similar materials.

The above mentioned hand protection is based on knowledge of the chemistry and anticipated uses of this product but it may not be appropriate for all workplaces. A hazard assessment should be conducted prior to use to ensure suitability of gloves for specific work environments and processes prior to use.

Eye protection

Use chemical splash goggles or face shield.

Skin and body protection

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

Hygiene measures

Avoid contact with skin, eyes and clothing. Do not inhale vapors or aerosols. Do not eat, drink, or smoke when using the product. Remove contaminated or saturated clothing.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

physical state liquid (20 °C) (1013 hPa)

Colour colorless
Form liquid
Odour aromatic

Odour Threshold not determined

Melting point/range < -100 °C

Method: OECD TG 102

Boiling point/range ca. 175 °C (1013 hPa)

Method: DIN 51 751

Flash point 57 °C

Method: DIN EN ISO 2719 (Pensky-Martens, Closed Cup)

Evaporation rate not determined

Lower explosion limit not determined

Upper explosion limit not determined

Vapour pressure 80 Pa (20 °C)

Method: AN-SOP 1024

pure substance

Density 0.89 g/cm3 (20 °C)

Method: DIN 51757

Water solubility not miscible

decomposition by hydrolysis

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 6 / 14



Partition coefficient: n-

not determined

octanol/water

Autoignition temperature not determined

Thermal decomposition not determined

Viscosity, dynamic not determined

9.2. Other information

Explosiveness Vapors can form explosive mixtures with air.

not explosive

Other information Vapors can form explosive mixtures with air.

10. Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No dangerous reactions known.

reactions

10.4. Conditions to avoid

Keep away from heat and sources of ignition.

10.5. Incompatible materials

water

10.6. Hazardous decomposition products

Ethanol in case of hydrolysis

11. Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity LD50 Rat: > 5110 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity LC50 Rat: > 27.892 mg/l / 4 h / Aerosol

Method: OECD Test Guideline 403
Test substance: Structurally similar substance

Molecular Weight corrected


Skin irritation Rabbit

irritating

Method: OECD Test Guideline 404

Eye irritation Rabbit

Dynasylan® PTEO





not irritating

Method: OECD Test Guideline 405

Sensitization Buehler Test guinea pig: No sensitizing effects.

Method: OECD Test Guideline 406
Test substance: Structurally similar substance

Repeated dose toxicity Oral Rat / 28-day

NOAEL: 940 mg/kg

Method: OECD Test Guideline 407
Test substance: Structurally similar substance

Molecular Weight corrected

Assessment of STOT single

exposure

Assessment The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Assessment of STOT repeat

exposure

Assessment The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Risk of aspiration toxicity No data available

Gentoxicity in vitro

Ames test Salmonella typhimurium

negative

Method: OECD TG 471

Test substance: Structurally similar substance

gene mutation TK +/- mouse lymphoma cell (L5178Y)

positive

Method: OECD TG 476

Test substance: Structurally similar substance

gene mutation TK +/- mouse lymphoma cell (L5178Y)

negative

Method: OECD TG 476

Test substance: Structurally similar substance

chromosomal aberration Chinese hamster (CHO K1 -cells)

positive

Method: OECD TG 473

Test substance: Structurally similar substance

chromosomal aberration Chinese hamster (CHO K1 -cells)

negative

Method: OECD TG 473

Test substance: Structurally similar substance

Gentoxicity in vivo Micronucleus test Mouse Oral

negative

Method: OECD TG 474


Test substance: Structurally similar substance

Micronucleus test Oral

negative

Method: OECD TG 474

Dynasylan® PTEO





Test substance: Structurally similar substance

Carcinogenicity No evidence that cancer may be caused.

Toxicity to reproduction 1 generation Oral Rat

NOAEL (No Observed > 940 mg/kg

Adverse Effect Level) of

parents:

NOAEL F1: > 940 mg/kg

Method: OECD Test Guideline 415
Test substance: Structurally similar substance

Molecular Weight corrected

Teratogenicity Oral Rat

NOAEL (No Observed > 940 mg/kg

Adverse Effect Level)

teratogenesis:

Method: OECD TG 414

Test substance: Structurally similar substance

Molecular Weight corrected

12. Ecological information

12.1. Toxicity

Toxicity to fish LC50 Brachy danio rerio: 80 mg/l / 96 h

Test substance: Structurally similar substance

Method: OECD TG 203

Toxicity in aquatic

invertebrates

EC50 Daphnia magna (Water flea): 21.5 mg/l / 48 h

Test substance: Structurally similar substance

Method: OECD TG 202

NOEC Daphnia magna (Water flea): > 100 mg/l / 21 d

Test substance: Structurally similar substance

Method: OECD 202 part 2

Toxicity to algae EC50 Desmodesmus subspicatus (green algae): > 819 mg/l / 72 h

Method: OECD TG 201

Toxicity to bacteria EC50 local activated sludge: > 100 mg/l / 3 h

Method: OECD TG 209

12.2. Persistence and degradability

Biodegradability Exposure time: 28 d

Result 54 % Not readily biodegradable.

Method: (DOC; Die Away test / 92/69/EEC part C.4-A)
Related to substance: Structurally similar substance

12.3. Bioaccumulative potential

Bioaccumulation Iow

120890

Dynasylan® PTEO

Material no.

Specification

Order Number

 Version
 4.0 / US

 Revision date
 05/23/2015

 Print Date
 08/18/2015

 Page
 9 / 14



12.4. Mobility in soil

Mobility Adsorption on the floor: low.

12.5. Other adverse effects

Further Information No ecotoxicological studies are available.

13. Disposal considerations

13.1. Waste treatment methods

Product

Waste must be disposed of in accordance with federal, state, provincial and local regulations.

Since empty containers retain product residue, follow MSDS and label warnings even after container is emptied.

Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

Uncleaned packaging

Do not reuse empty containers and dispose of in accordance with the regulations issued by the appropriate local authorities.

If there is product residue in the emptied container, follow directions for handling on the container's label.

Incorrect disposal or reuse of this container is illegal and can be dangerous.

Other countries: observe the national regulations.

14. Transport information

D.O.T. Road/Rail

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Propyltriethoxysilane)

14.3. Trans port hazard class(es): 3
14.4. Packing group: III
14.5. Environmental hazards (Marine pollutant): --

14.6. Special precautions for user: Yes

ROAD: In the U.S. this material may be classified as combustible liquid. Combustible liquid are not regulated in packages 450 liters or less. This applies for shipments by road and rail only

RAIL: In the U.S. this material may be classified as combustible liquid. Combustible liquids are (CFR) not regulated in packages 450 liters or less. This applies for shipments by road and rail

only.

Air transport ICAO-TI/IATA-DGR

14.1. UN number: UN 1993

14.2. UN proper shipping name: Flammable liquid, n.o.s.(Propyltriethoxysilane)

14.3. Trans port hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

14.6. Special precautions for user:

Yes

Dynasylan® PTEO



 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 10 / 14

IATA-C: ERG-Code 3L

Maximum Net Quantity per Package 220 L

IATA-P: ERG-Code 3L

Maximum Net Quantity per Package 60 L

Sea transport IMDG-Code/GGVSee (Germany)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Propyltriethoxysilane)

14.3. Transport hazard class(es):
14.4. Packing group:
14.5. Environmental hazards (Marine

pollutant):

14.6. Special precautions for user: No EmS: F-E,S-E

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

for transportapproval see regulatory information

15. Regulatory information

US Federal Regulations

OSHA

If listed below, chemical specific standards apply to the product or components:

None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

None listed

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

None listed

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Fire Hazard
- Acute Health Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

None listed

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 11 / 14



Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

None listed

State Regulations

The Listing requirements of the Right to Know (RTK) legislation varies by state. All information for NJ, PA, MA and other states can be derived from the listing of hazardous and non-hazardous components in section 2 and 15 of this MSDS.

California Proposition 65

A warning under the California Drinking Water Act is required only if listed below:

None listed

An employer using HMIS/NFPA labeling must through training ensure that its employees are fully aware of the hazards of the chemicals used.

HMIS Ratings

Health: 1 Flammability: 2 Physical Hazard: 1

NFPA Ratings

Health: 1
Flammability: 2
Reactivity: 1

16. Other information

Further information

Revision date 05/23/2015

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Dynasylan® PTEO

 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 12 / 14



This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Dynasylan® PTEO



 Material no.
 Version Revision date
 4.0 / US

 Specification
 120890
 Print Date
 08/18/2015

 Order Number
 Page
 13 / 14

Legend

ACC American Chemistry Council

ACGIH American Conference of Governmental Industrial Hygenists

ACS Advisory Committee on Sustainability

ADI Acceptable Daily Intake

ASTM American Society for Testing and Materials

ATP Adaptation to Technical Progress

BCF Bioconcentration factor
BOD Biochemical oxygen demand

c.c. closed cup

CAO Cargo Aircraft Only

Carc Carcinogen

CAS Chemical Abstract Services

CDN Canada

CEPA Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response – Compensation and Liability Act

CFR Code of Federal Regulations

CMR carcinogenic-mutagenic-toxic for reproduction

COD Chemical oxygen demand

DIN German Institute for Standardization
DM EL Derived minimum effect level
DNEL Derived no effect level
DOT Department of Transportation
EC50 half maximal effective concentration
EPA Environmental Protection Agency
ErC50 Reduction of Growth Rate

ERG Emergency Response Guide Book FDA Food and Drug Administration

GHS Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

GLP Good Laboratory Practice
GMO Genetic Modified Organism
HCS Hazard Communication Standard

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer
IATA International Air Transport Association

IBC Intermediate Bulk Container

ICAO-TI International Civil Aviation Organization- Technical Instructions

ICCA International Council of Chemical Association

ID Identification number

IMDG International Maritime Dangerous Goods

IUPAC International Union of Pure and Applied Chemistry
ISO International Organization For Standardization

LC50 50 % Lethal Concentration

LD50 50 % Lethal Dose **L(E)C50** LC50 or EC50

LOA EL Low est observed adverse effect level

LOEL Low est observed effect level

MARPOL International Convention for the Prevention of Pollution from Ships

NFPA National Fire Protection Association
NOAEL No observed adverse effect level
NOEC no observed effect concentration

NOEL no observed effect level

o. c. open cup

OECD Organisation for Economic Cooperation and Development

OEL Occupational Exposure Limit

OSHA Occupational Safety and Health Administration

PBT Persistent, bioaccumulative, toxic
PEC Predicted effect concentration
PNEC Predicted no effect concentration

RQ Reportable Quantity SDS Safety Data Sheet

STOT Specific Target Organ Toxicity

UN United Nations

vPvB very persistent, very bioaccumulative

Dynasylan® PTEO

Version 4.0 / US Material no. 05/23/2015 Revision date Specification 120890 Print Date 08/18/2015 Order Number Page 14/14



voc

volatile organic compounds Workplace Hazardous Materials Information System WHMIS

WHO World Health Organization