



Product Information

19.07.2021

GLICERODAC WS 180 VG

Composition

Glycerol, ethoxylated and propoxylated

Product data (specification)

Property	Value	Unit	Test method
Appearance at 20 °C	liquid, clear	-	visual
APHA colour number	≤ 300	mg Pt/l	DIN EN 1557
Cloud point (10% in 25 %iger BDG)	40 - 45	°C	DIN EN 1890
pH value (5% in demin. water)	5 - 7	-	DIN EN 1262

General product description

Property	Value	Unit	Test method
Density at 20 °C	about 1.018	g/ml	DIN 51757
Flash point	> 125	°C	DIN 51376
Pour Point	< - 30	°C	ASTM D 5985
Kin. Viscosity at 40 °C	214	mm ² /s	ASTM D 7042
Water	< 0.25	% by mass	DIN EN 13267

Transport and packaging

Road tankcar, about 200 kg drums, about 1000 kg containers

Storage

Stainless steel vessels (Steel No.: 1.4541 or 1.4571)

This information is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party patent rights. In particular, no guarantee of properties in the legal sense is implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Reference to trade names used by other companies is neither a recommendation, nor is it intended to suggest that similar products could not be used. All our business transactions shall exclusively be governed by our General Sales Conditions.

Sasol Germany GmbH

Anckelmannsplatz 1, 20537 Hamburg Postanschrift: Postfach 26 18 05, 20508 Hamburg
Telefon: +49 40 63 684-1000 Telefax: +49 40 63 684-3700 info@de.sasol.com www.sasol.com
Geschäftsführung: Dr. Jens Straatmann, Judith Hübner Vorsitzender des Aufsichtsrats: Christian Schindler
Sitz der Gesellschaft: Hamburg Registergericht: Amtsgericht Hamburg HRB 78475