



ADHESIVES

SYNTHETIC
POLYMERS

ELVACE[®] 757

DESCRIPTION

A surfactant stabilized vinyl acetate-ethylene copolymer emulsion

APPLICATION

A medium-soft, surfactant stabilized copolymer designed for applications such as specialty adhesives, caulks, sealants and coatings.

FEATURES

- ◆ Excellent adhesion
- ◆ Very good water resistance
- ◆ Tough, permanently flexible polymer films
- ◆ Excellent filler acceptance
- ◆ Good UV resistance
- ◆ Low residual VAM

PROPERTIES

Nonvolatile content, %	63.5 - 65.5
pH	4.5 - 5.5
Viscosity, #2 @ 20 @ 25°C	700 cps
Weight, U.S., Lbs./Gal.	8.8 - 9.1
Tg, °C by DSC	0
MFFT, °C	-2
Borax stable	Yes

STORAGE

Protect from freezing. Ideal storage temperature is 72°F. Stability at 72°F is >180 days.

SHIPPING FORM

Available in 10,000- or 20,000-gallon railroad tank cars, 5,000-gallon tank trucks, totes or 55- gallon non-returnable fiber drums.

**READ THE ELVACE[®] 757 MATERIAL SAFETY DATA
SHEET BEFORE HANDLING, STORING, OR USING THIS PRODUCT**

RV 1/07

Forbo Adhesives, LLC • Synthetic Polymers • P.O. Box 110447 • Durham, NC 27709

800 711-2417

The information herein is general information designed to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents and suitability for their specific applications. We warrant that our products will meet our written specifications. **Nothing herein shall constitute any other warranty express or implied, including any warranty of merchantability or fitness for a particular purpose,** nor is any protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.