







PRODUCT PROFILE

P353 is a cost-effective opacifying agent for pipe monolayer films and moulding applications requiring low weatherability. Due to low grit content, the product provides low filterability index and offers good dispersibility.

P353 is also used in synthetic paints application which demands blue undertone. This product is commonly used as a supplementary carbon source for graphitized products, such as carbon brushes.

The dispersibility of P353 depends on the equipment used and the formulation.

TYPICAL VALUE

NSA	STSA	OAN	Tint Strength	Sieve Residue	Heating Loss
m²/g	m²/g	cc/100g	% ITRB	325M, ppm	(As Shipped) %
35	33	90	60	45	0.6

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
Plastic Masterbatches	Upto 52%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging 25kg paper bag or 500/1000kg bulk bag

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcblltd.com | E: pcbl.specialtyblack@rpsg.in

Revision No. - 01 Issue - Nov. 2022







