



## PRODUCT DATA SHEET

### KRYSTOL™ 350

TEST DESCRIPTION	METHOD	SPECIFICATIONS		TYPICAL
Product Code				KRSTL35
		<b>MIN</b>	<b>MAX</b>	
Density, kg/L at 15 °C	ASTM D4052	Report		0.867
Specific Gravity at 25°C	ASTM D4052	0.850	0.880	0.864
Kinematic Viscosity, cSt at 40 °C	ASTM D445	65	72	67
Saybolt Universal Viscosity at 100°F	ASTM D2161	Report		340
Appearance, Visual	LORM 004	Clear & Bright		Clear & Bright
Flash point, C O C, ° C (° F)	ASTM D92			271
Colour, Saybolt	ASTM D156	+28		>30
Meets UV Absorbance-CFR 178.3620 (b)	ASTM D2269	PASS		PASS

Date Issued: 1/18/2011  
Date Reviewed: 1/29/2021

KRYSTOL 350 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA), 21 CFR 178.3620(b) Technical White Mineral Oil
- Certified Kosher Pareve
- Certified Halal
- Expiry Date from Date of Manufacture is 3 years

**Petro-Canada Lubricants Inc.**

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

[lubricants.petro-canada.com](http://lubricants.petro-canada.com)