



# PRODUCT DATA SHEET

## KRYSTOL™ 150

| TEST DESCRIPTION                     | METHOD     | SPECIFICATIONS |            | TYPICAL        |
|--------------------------------------|------------|----------------|------------|----------------|
| Product Code                         |            |                |            | KRSTL15        |
|                                      |            | <b>MIN</b>     | <b>MAX</b> |                |
| Density, kg/L at 15 °C               | ASTM D4052 | Report         |            | 0.8613         |
| Specific Gravity at 25°C             | ASTM D4052 | 0.845          | 0.870      | 0.8575         |
| Specific Gravity @ 60°F              | ASTM D4052 | Report         |            | 0.8564         |
| Wt. / Gal. @ 60°F                    | #N/A       | Report         |            | 7.13           |
| Kinematic Viscosity, cSt at 40 °C    | ASTM D445  | 28.5           | 30.5       | 29.55          |
| Flash point, C O C, ° C (° F)        | ASTM D92   | 200            |            | 207 (405)      |
| Appearance, Visual                   | LORM 004   | Clear & Bright |            | Clear & Bright |
| Colour, Saybolt                      | ASTM D156  | +28            |            | >30            |
| Meets UV Absorbance-CFR 178.3620 (b) | ASTM D2269 | PASS           |            | PASS           |

Date Issued: 1/18/2011  
Date Reviewed: 1/29/2021

KRYSTOL 150 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA), 21 CFR 178.3620(b) Technical White Mineral Oil
- Certified Kosher Pareve
- Certified Halal
- Expiry Date from Date of Manufacture is 3 years

**Petro-Canada Lubricants Inc.**

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

[lubricants.petro-canada.com](http://lubricants.petro-canada.com)