

## SAFETY DATA SHEET

---

### 1. IDENTIFICATION

<b>Product Name:</b>	<b>EBECRYL® 745 radiation curing resins</b>
<b>Synonyms:</b>	None
<b>Product Description:</b>	Acrylic resin in acrylic monomers
<b>Molecular Formula:</b>	Mixture
<b>Molecular Weight:</b>	Mixture
<b>Intended/Recommended Use:</b>	Radiation curable coating ingredient, Coatings & Inks
<b>Uses advised against:</b>	This product should not be used in any application where unreacted liquid product is intended to come in direct contact with skin or nails. Reason: sensitizing properties.

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

**For Product and all Non-Emergency Information call** your local Allnex contact point or contact us at <http://www.allnex.com/contact>

**EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:**

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)

See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ® , TM or \* as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

---

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Carcinogenicity Hazard Category 2

Specific Target Organ Toxicity - Single Exposure Hazard Category 3

Skin Corrosion / Irritation Hazard Category 2

Serious Eye Damage / Eye Irritation Hazard Category 2A

Skin Sensitizer Hazard Category 1B

Aquatic Environment Acute Hazard Category 2

Aquatic Environment Chronic Hazard Category 2

#### LABEL ELEMENTS



**Signal Word**  
WARNING

**Hazard Statements**

Suspected of causing cancer  
 May cause drowsiness or dizziness  
 May cause respiratory irritation  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 Toxic to aquatic life  
 Toxic to aquatic life with long lasting effects

### Precautionary Statements

Obtain special instructions before use.  
 Use only outdoors or in a well-ventilated area.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Avoid release to the environment.  
 IF exposed or concerned: Get medical advice/attention.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Specific treatment (see supplemental first aid instructions on this label).  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.  
 Dispose of contents/container in accordance with local and national regulations.

### Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification
Tripropylene glycol diacrylate 42978-66-5	15 - 25	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic Acute 2 (H401) Aquatic Chronic 2 (H411)
Hexamethylene diacrylate 13048-33-4	15 - 25	Skin Irrit. 2 (H315) Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)
Phosphorous acid, triphenyl ester 101-02-0	< 0.6	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
N-Vinyl-2-pyrrolidone 88-12-0	0.1 - 0.3	Carc. 2 (H351) Acute Tox. 4 (H302) Acute Tox. 4 (H312)

		Acute Tox. 4 (H332) STOT RE 2 (H373) STOT SE 3 (H335) Eye Dam. 1 (H318)
--	--	--

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

---

## 4. FIRST AID MEASURES

### First-aid Measures

**Inhalation:**

Remove to fresh air. If breathing is difficult, give oxygen. Apply artificial respiration if patient is not breathing. Obtain medical attention immediately.

**Skin Contact:**

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

**Eye Contact:**

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

**Ingestion:**

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

**Most Important Symptoms and Effects, Acute and Delayed**

None known.

**Immediate Medical Attention and Special Treatment**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Notes To Physician:**

No specific measures have been identified.

---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:**

Use water spray or fog, carbon dioxide or dry chemical.

**Unsuitable Extinguishing Media:**

high pressure water jet.

**Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

**Special Hazards:**

Keep containers cool by spraying with water if exposed to fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

### Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

### Environmental Precautions:

Use appropriate containment to avoid environmental contamination. Avoid release to the environment.

### References to other sections:

See Sections 7, 8 and 13 for additional information.

---

## 7. HANDLING AND STORAGE

### HANDLING

**Precautions:** Avoid release to the environment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid breathing vapors or spray mist. Wear protective gloves and eye/face protection.

**Special Handling Statements:** Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

### STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

**Storage Temperature:** Store at 4 - 40 °C

**Reason:** Quality.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

### Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

#### Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

### Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

### Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing. Barrier creams may be used in conjunction with the gloves to provide additional skin protection.

**Hand Protection:**

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

Gloves for short term exposure/splash protection - non exhaustive list:

Laminated multilayer gloves, break through time: > 60 min

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: < 60 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

**Additional Advice:**

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

---

**Exposure Limit(s)****88-12-0 N-Vinyl-2-pyrrolidone**

OSHA (PEL):	Not established
ACGIH (TLV):	0.05 ppm (TWA)
Other Value:	Not established

**Biological Exposure Limit(s)**

No values have been established.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Color:</b>	yellowish
<b>Appearance:</b>	liquid
<b>Odor:</b>	ester acrylate
<b>Boiling Point:</b>	> 100 °C
<b>Melting Point:</b>	Not available
<b>Vapor Pressure:</b>	0.013 hPa @ 20 °C
<b>Specific Gravity/Density:</b>	1.05 g/cm <sup>3</sup>
<b>Vapor Density:</b>	Not available
<b>Percent Volatile (% by wt.):</b>	< 0.3 %
<b>pH:</b>	Not available
<b>Saturation In Air (% By Vol.):</b>	Not available
<b>Evaporation Rate:</b>	Not available
<b>Solubility In Water:</b>	Not available
<b>Volatile Organic Content:</b>	Not available
<b>Flash Point:</b>	150 °C Cleveland Open Cup
<b>Flammable Limits (% By Vol):</b>	Not available

<b>Autoignition Temperature:</b>	Not available
<b>Decomposition Temperature:</b>	Not available
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>Odor Threshold:</b>	Not available
<b>Viscosity (Kinematic):</b>	Not applicable
<b>Viscosity (Dynamic):</b>	15000 - 25000 mPa.s @ 25 °C
<b>Flammability:</b>	Normal combustion
<b>Oxidizing Properties:</b>	Not available

---

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	No information available
<b>Stability:</b>	Stable.
<b>Conditions To Avoid:</b>	Avoid direct exposure to sunlight. Avoid temperatures higher than 60°C. Avoid friction with temperature increase as result. Avoid exposure to strong UV sources. Loss of dissolved air. Loss of polymerization inhibitor. Avoid direct contact with heat sources.
<b>Polymerization:</b>	May occur
<b>Conditions To Avoid:</b>	Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers. Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated.
<b>Materials To Avoid:</b>	Avoid contact with peroxides. Avoid free radical producing initiators. Avoid contact with reactive metals. Contact with alkalis. They give an exothermic reaction with the product. Unintentional contact with them should be avoided.
<b>Hazardous Decomposition Products:</b>	Carbon dioxide Carbon monoxide (CO)

---

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Skin, Eyes, Oral, Respiratory System.

**Acute toxicity - oral:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - dermal:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - inhalation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin corrosion / irritation:** Causes skin irritation

**Serious eye damage / eye irritation:** Causes serious eye irritation

**Respiratory sensitization:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin sensitization:** May cause an allergic skin reaction

**Carcinogenicity:** Suspected of causing cancer

**Germ cell mutagenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Reproductive toxicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure:** May cause drowsiness or dizziness. May cause respiratory irritation.

**Specific target organ toxicity (STOT) - repeated exposure:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Aspiration hazard:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

## PRODUCT TOXICITY INFORMATION

### ACUTE TOXICITY DATA

oral	rat	Acute LD50	> 2000 mg/kg
dermal	rabbit	Acute LD50	> 2000 mg/kg
inhalation	rat	Acute LC50 4 hr	> 5 mg/l (Dust/Mist)

### LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	Skin	rabbit	Irritating
Acute Irritation	eye	rabbit	Irritating

### ALLERGIC SENSITIZATION

Sensitization	Skin	Sensitizing
Sensitization	respiratory	No data

### GENOTOXICITY

#### Assays for Gene Mutations

Ames Salmonella Assay	Salmonella Typhimurium Escherichia coli	Not mutagenic, (tested)
-----------------------	---	-------------------------

### OTHER INFORMATION

The product toxicity information above has been estimated.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

### HAZARDOUS INGREDIENT TOXICITY DATA

Tripropylene glycol diacrylate has acute oral (rat) LD50 and acute dermal (rabbit) LD50 values of >2000 mg/kg, respectively. Direct contact causes skin and eye irritation. Repeated contact may cause skin sensitization (allergic skin reaction). Based on a weight of evidence approach, there is no genotoxic potential. No target organ toxicity was observed in repeated dose toxicity studies via oral and dermal route. Reproductive performance was not impaired in an extended one generation study with rats, nor were developmental effects observed in prenatal studies with rats and rabbits.

Hexamethylene diacrylate, CAS 13048-33-4, has oral (rat) and dermal (rabbit) LD50 values of >5000 mg/kg and 3600 mg/kg, respectively. This material causes moderate skin and eye irritation. Repeated skin contact may cause

allergic skin reaction. No evidence of point mutations in the Salmonella bacterial test was observed. Structurally similar acrylate and methacrylate substances showed no evidence of point mutation in the in vitro hprt mutation assay and no evidence of a mutagenic effect was seen when tested in whole animal chromosomal aberration and/or micronucleus assays. In contrast this substance as well as the entire acrylate/methacrylate chemical class produced a consistently positive response when tested in the mouse lymphoma assay and/or other in vitro mammalian cell assays designed to detect clastogenicity. However, the biological relevance of this in vitro response is questioned as these results could not be confirmed in tests on whole mammalian systems. This substance has been shown to cause fetotoxic effects during animal testing only in the presence of maternal toxicity.

Phosphorous acid, triphenyl ester may cause serious eye and moderate skin irritation. The oral, dermal and inhalation LD50 values for the rat are 1590 mg/kg, > 2000 mg/kg and > 5mg/l (dust/mist) respectively. Sensitization has been observed after dermal exposure. No mutagenicity could be evidenced in in-vitro testing. There is no experimental evidence for adverse effects in reproduction. There is no experimental evidence of carcinogenic effect.

Vinylpyrrolidone has an acute oral (rat) LD50, acute dermal (rabbit) LD50 and 4-hour inhalation values of 1022 to 1470 mg/kg, 1043 mg/kg and 3.2 mg/L, respectively. Vinylpyrrolidone is harmful by inhalation, in contact with skin and if swallowed. This material produces severe eye irritation in animal tests. Prolonged exposure might lead to irritancy of the respiratory tract and other chronic diseases – including tumor formation. No genotoxic effects were observed in in vitro or animal studies. Vinylpyrrolidone has shown teratogenic effects.

### Carcinogenicity

This product contains one or more Carcinogen Chemical(s) in accordance with IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), ACGIH (American Conference of Governmental Industrial Hygienists).

Component / CAS No.	Carcinogen
N-Vinyl-2-pyrrolidone 88-12-0	ACGIH A3



**WARNING:** Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## 12. ECOLOGICAL INFORMATION

### TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

**Overall Environmental Toxicity:** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

The ecological assessment for this material is based on an evaluation of its components.

### RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

### HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Tripropylene glycol diacrylate	LC50 = 4.6 - 10 mg/L - <i>Leuciscus idus melanotous</i>



(42978-66-5)	(96h)
Hexamethylene diacrylate (13048-33-4)	LC50 = 4.6 - 10 mg/L - <i>Leuciscus idus</i> (96hrs) LC50 = 0.38 mg/L - <i>Oryzias latipes</i> (96hrs) NOEC = 0.072 mg/L - <i>Oryzias latipes</i> (39d)
Phosphorous acid, triphenyl ester (101-02-0)	Not available
N-Vinyl-2-pyrrolidone (88-12-0)	Not available

Component / CAS No.	Toxicity to Water Flea
Trippropylene glycol diacrylate (42978-66-5)	EC50 = 89 mg/L - <i>Daphnia magna</i> (48h)
Hexamethylene diacrylate (13048-33-4)	EC 50 = 2.6 mg/L - <i>Daphnia magna</i> (48hrs) EC50 = 2.7 mg/L - <i>Daphnia magna</i> (48hrs) NOEC = 0.14 mg/L - <i>Daphnia magna</i> (21d)
Phosphorous acid, triphenyl ester (101-02-0)	Not available
N-Vinyl-2-pyrrolidone (88-12-0)	EC50 = 45 mg/L - <i>Daphnia</i> species (48h)

Component / CAS No.	Toxicity to Algae
Trippropylene glycol diacrylate (42978-66-5)	EC50 = 69.5 mg/L - <i>Scenedesmus subspicatus</i> (72h)
Hexamethylene diacrylate (13048-33-4)	EC 50 = 1.5 mg/L - <i>Desmodesmus subspicatus</i> (72hrs) NOEC = 0.5 mg/L - <i>Desmodesmus subspicatus</i> (72hrs) EC50 = 2.33 mg/L - <i>Selenastrum capricornutum</i> (72hrs) NOEC = 0.9 mg/L - <i>Selenastrum capricornutum</i> (72hrs)
Phosphorous acid, triphenyl ester (101-02-0)	Not available
N-Vinyl-2-pyrrolidone (88-12-0)	EC50 = 780 mg/L - <i>Desmodesmus subspicatus</i> (72h)

Component / CAS No.	Partition coefficient
Trippropylene glycol diacrylate (42978-66-5)	2.77
Hexamethylene diacrylate (13048-33-4)	Log Kow = 2.81
Phosphorous acid, triphenyl ester (101-02-0)	4.98
N-Vinyl-2-pyrrolidone (88-12-0)	0.4

### 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change.

State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

---

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

### US DOT

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: III

UN/ID Number: UN3082

Transport Label Required:       Miscellaneous  
  Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIPROPYLENE GLYCOL DIACRYLATE, TRIPHENYLPHOSPHITE

Comments:                               Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

### TRANSPORT CANADA

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: III

UN Number: UN3082

Transport Label Required:       Miscellaneous  
  Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIPROPYLENE GLYCOL DIACRYLATE, TRIPHENYLPHOSPHITE

### ICAO / IATA

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9

Packing Group: III

UN Number: UN3082

Transport Label Required:       Miscellaneous

TECHNICAL NAME (N.O.S.): TRIPROPYLENE GLYCOL DIACRYLATE, TRIPHENYLPHOSPHITE

### IMO

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9

UN Number: UN3082

Packing Group: III

Transport Label Required: Miscellaneous  
Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIPROPYLENE GLYCOL DIACRYLATE, TRIPHENYLPHOSPHITE

### SPECIAL PRECAUTIONS FOR USER

Protect against external heat sources above +40°C/104°F.

---

## 15. REGULATORY INFORMATION

### Inventory Information

**United States (USA):** All components of this product are designated as “Active” on the TSCA Inventory or are not required to be listed.

**Canada:** All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

**European Economic Area (including EU):** When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

**Australia:** All components of this product are included in the Australian Inventory of Industrial Chemicals (AIIC) or are not required to be listed on AIIC.

**New Zealand:** This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

**China:** All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

**Japan:** One or more components of this product are NOT included on the Japanese (ENCS and/or ISHL) inventories.

**Korea:** All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

**Philippines:** All components of this product are either listed on the Philippine (PICCS) inventory, have been assessed by Environmental Management Bureau (EMB) or are exempt from notification requirements.

**Taiwan:** All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

**Switzerland:** All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 24-26).

**Turkey:** When purchased directly from Allnex by a Turkish legal entity, this product is compliant with the PRE-registration requirements of KKDIK as all its components are either pre-registered, excluded and/or exempt.

### OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40

CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

## PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

### Physical Hazards

Not applicable

### Health Hazards

Carcinogenicity

Skin Corrosion or Irritation

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

---

## 16. OTHER INFORMATION

### NFPA Hazard Rating (National Fire Protection Association)

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

**Reasons for Issue:** Revised Section 2  
Revised Section 3  
Revised Section 8  
Revised Section 11

**Date Prepared:** 01/22/2021

**Date of last significant revision:** 01/22/2021

### Component - Hazard Statements

Tripropylene glycol diacrylate

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

Hexamethylene diacrylate

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H400 - Very toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

Phosphorous acid, triphenyl ester

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

N-Vinyl-2-pyrrolidone

H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

H318 - Causes serious eye damage.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.

### Emergency phone numbers for other regions

#### Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia)  
China (PRC): +86(0)532 8388 9090 (NRCC)  
India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)  
Indonesia: 007 803 011 0293 (Carechem 24)  
Japan: +81 345 789 341 (Carechem 24)  
Korea: +82 2 3479 8401 (Carechem 24)  
Malaysia: +60 3 6207 4347 (Carechem 24)  
New Zealand: +64 0800 803 002 (Allnex New Zealand)  
Philippines: +63 2 231 2149 (Carechem 24)  
Taiwan: +886 2 8793 3212 (Carechem 24)  
Vietnam: +84 8 4458 2388 (Carechem 24)  
All Others: +65 3158 1074 (Carechem 24)

#### Europe

+44 (0) 1235 239 670 (Carechem 24)

#### Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

#### Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)  
Chile: +56 2 2582 9336 (Carechem 24)  
Mexico and all others: +52-555-004-8763 (Carechem 24)

---

Prepared By: Product Stewardship & Regulatory Affairs Department, <http://www.allnex.com/contact>

---

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

---