



PRODUCT DATA SHEET

KRYSTOL™ 550

| TEST DESCRIPTION | METHOD | SPECIFICATIONS | | TYPICAL |
|--------------------------------------|------------|----------------|------------|----------------|
| Product Code | | | | KRSTL55 |
| | | MIN | MAX | |
| Density, kg/L at 15 °C | ASTM D4052 | Report | | 0.871 |
| Specific Gravity at 25°C | ASTM D4052 | 0.860 | 0.880 | 0.867 |
| Kinematic Viscosity, cSt at 40 °C | ASTM D445 | 90.0 | 125.0 | 104 |
| Saybolt Universal Viscosity at 100°F | ASTM D2161 | Report | | 477 |
| Appearance, Visual | LORM 004 | Clear & Bright | | Clear & Bright |
| Colour, Saybolt | ASTM D156 | +28 | | >30 |
| Pour Point, °C (°F) | ASTM D5950 | | -9(16) | -15(5) |
| Flash point, C O C, ° C (° F) | ASTM D92 | 250(482) | | 273 (523) |
| GC Distillation, 5%, ° C (° F) | ASTM D2887 | 430(806) | | 436 (817) |

Date Issued: 1/18/2011
Date Reviewed: 1/29/2021

KRYSTOL 550 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA), 21 CFR 178.3620(b) Technical White Mineral Oil
- Certified Kosher Pareve
- Certified Halal
- Expiry Date from Date of Manufacture is 3 years

Petro-Canada Lubricants Inc.

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

lubricants.petro-canada.com