

BLUESIL EMUL 9500

Description	BLUESIL™ EMUL 9500 is a general purpose, silicone emulsion of silanol terminated polysiloxane polymers. BLUESIL™ EMUL 9500 can be used as is or in conjunction with a tin catalyst to make a fully crosslinkable coating.	
Examples of applications	Please consult your local ELKEM SILICONES sales office.	
Key benefits	<ul style="list-style-type: none"> • Easy Release • Better attachment to polar surfaces than standard dimethylsiloxanes • Good bath life 	
Typical properties		BLUESIL EMUL 9500
	Viscosity ISO 2555	< 1800 cP
	Appearance	Milky white liquid
	Solids, %	40
	Specific gravity @ 25°C	1.0
	pH	6
	Please note: The typical properties are not intended for use in preparing specifications. Please contact our local Sales Department for assistance in writing specifications.	
Instruction of use	Please consult your local ELKEM SILICONES sales office.	
Regulation	Please consult your local ELKEM SILICONES sales office.	
Limitations	Please consult your local ELKEM SILICONES sales office.	
Packaging	<ul style="list-style-type: none"> • BLUESIL EMUL 9500 is available in <ul style="list-style-type: none"> ○ Drum of 200 KG (441 LB) ○ Pail of 20 KG (44.1 LB) 	
Storage and shelf life	When stored in its original packaging: BLUESIL EMUL 9500 may be stored for up to 6 months from its date of manufacturing. Comply with the storage instructions and expiration date marked on the packaging. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.	
Safety	Please consult the Safety Data Sheet of: BLUESIL EMUL 9500	

Visit our website www.elkem.com/silicones/

Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.