



B 1473

PRODUCT INFORMATION

Description

Ba / Zn Liquid Stabilizer

Typical Properties

Appearance:	Clear Amber Liquid
Specific gravity at 20°C:	1.015 – 1.045 g/cm ³
Refractive Index at 20°C:	1.4868 – 1.4928

Application

B 1473 is a highly efficient Ba/Zn liquid stabilizer with very good heat stability for use in flexible to semi-rigid PVC compounds. It has mild lubrication and can be used with or without additional lubricants.

B 1473 is designed for applications requiring excellent color hold under dynamic stress and is suitable for most production processes but especially for calendaring and extrusion of plasticized printable films.

For printable applications it is recommended to keep the use level low and extend heat stability by incorporating epoxidized soybean oil.

Recommended dosage: 1.5 to 3.0 phr, depending on application.

Food Packaging Approval

B 1473 may not be used for the manufacturing of food packaging materials.

Handling

A material safety data sheet for the handling of this product is available on request.

Storage

Storage at room temperature is recommended.
Liquid products may be affected by moisture and containers should be kept tightly closed.

The data herein is deemed accurate by the supplier, however, is provided for informational purposes only and creates no warranties, express or implied. As the consumer controls application of the product, this information does not constitute a warranty of merchantability, fitness for a particular use or recommendations to practice any patented invention without a license.