

# Filtered Neutral Oil

## Technical Data Sheet



**Product Identification** Filtered Neutral Oil is a refined grade of castor oil having a very low acid value making this product ideal for applications where a low acid value is required.

Filtered Neutral Oil is also available as DRY – FNO with a moisture content of 0.02% maximum.

	<u>Property</u>	<u>Value</u>
<b>Physical Properties</b>	<b>Composition</b>	Approximately, 90% Triglyceride of Ricinoleic Acid
	<b>Molecular Weight</b>	928
	<b>Form</b>	Clear viscous hazy liquid
	<b>Acid Value</b>	0.5
	<b>Color, Gardner</b>	1
	<b>Density, lbs./gal, 25°C</b>	7.98
	<b>Fire Point, COC, °F</b>	605
	<b>Flash Point, COC, °F</b>	555
	<b>Hydroxyl Value</b>	164
	<b>Iodine Value</b>	86
	<b>Moisture Content, %</b>	0.2
	<b>Pour Point, °F</b>	-10
	<b>Refractive Index</b>	1.4775
	<b>Saponification Value</b>	180
	<b>Specific Gravity, 25°C/25°C</b>	0.959
<b>Viscosity, 25°C, Stokes</b>	7.3	

- Applications**
- Polyurethane Systems
  - Lubricants
  - Chemical Intermediates
  - Soluble in alcohols (hot), esters, ethers, ketones and aromatic hydrocarbons
  - Partially soluble in aliphatic hydrocarbons, insoluble in water

For toxicity or regulatory information please consult the Material Safety Data Sheet.

*Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.*

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA  
USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com  
Web: [www.vertellus.com](http://www.vertellus.com)