

# **SAFETY DATA SHEET**

**BLUE CUBE OPERATIONS LLC** 

Product name: D.E.R.\* 727 Epoxy Diluent Issue Date: 03/07/2016

Print Date: 07/31/2018

BLUE CUBE OPERATIONS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# 1. IDENTIFICATION

Product name: D.E.R.\* 727 Epoxy Diluent

Recommended use of the chemical and restrictions on use

**Identified uses:** Reactive diluent.

**COMPANY IDENTIFICATION** 

BLUE CUBE OPERATIONS LLC 190 CARONDELET PLAZA, SUITE 1530 CLAYTON MO 63105-3467 UNITED STATES

Customer Information Number: +1 844-238-3445 INFO@OLINBC.com

**EMERGENCY TELEPHONE NUMBER** 

**24-Hour Emergency Contact:** 1 800 424 9300 **Local Emergency Contact:** 1 800-424-9300

## 2. HAZARDS IDENTIFICATION

#### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Skin irritation - Category 2 Eye irritation - Category 2A Skin sensitisation - Sub-category 1A

# Label elements Hazard pictograms



Product name: D.E.R.\* 727 Epoxy Diluent

Signal word: WARNING!

#### **Hazards**

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

#### **Precautionary statements**

#### Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear eye protection/ face protection.

Wear protective gloves.

#### Response

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

Collect spillage.

### **Disposal**

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

No data available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: p-tert-Butylphenyl glycidylether

This product is a substance.

Component CASRN Concentration

4-tert-Butylphenyl glycidyl ether 3101-60-8 100.0%

# 4. FIRST AID MEASURES

### Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

Page 2 of 11

**Skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

**Ingestion:** If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

#### Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolics. Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is emitted when burned without sufficient oxygen.

#### **Advice for firefighters**

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, applied gently may be used as a blanket for fire extinguishment. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Page 3 of 11

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep upwind of spill. Ventilate area of leak or spill. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to section 7, Handling, for additional precautionary measures.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Collect in suitable and properly labeled containers. Absorb with materials such as: Sand. See Section 13, Disposal Considerations, for additional information.

Removal of ignition sources: Keep away from sources of ignition.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**Conditions for safe storage:** Store in a cool, dry place.

Storage stability

Storage temperature: Shelf life: Use within 2 - 43 °C (36 - 109 °F) 12 Month

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

Exposure limits are listed below, if they exist.

Exposure limits have not been established for those substances listed in the composition, if any have been disclosed.

#### **Exposure controls**

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

## **Individual protection measures**

**Eye/face protection:** Use safety glasses (with side shields). **Skin protection** 

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Nitrile/butadiene rubber ("nitrile" or "NBR"). Viton. Avoid gloves made of: Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state
Color
Colorless
Odor
Characteristic
Odor Threshold
PH
No data available

Freezing point No test data available

**Boiling point (760 mmHg)**  $> 250 \, ^{\circ}\text{C} \, (> 482 \, ^{\circ}\text{F}) \, \textit{Literature}$ 

Flash point closed cup 130 °C (266 °F) Literature

**Evaporation Rate (Butyl Acetate** No test data available

= 1)

Flammability (solid, gas) Not Applicable

Lower explosion limitNo test data availableUpper explosion limitNo test data available

Vapor Pressure < 1 hPa at 20 °C (68 °F) Literature

Relative Vapor Density (air = 1) No test data available

Relative Density (water = 1) 1.02 at 20 °C (68 °F) Literature

Product name: D.E.R.\* 727 Epoxy Diluent

Water solubility < 0.1 % *Literature* immiscible

Partition coefficient: n- log Pow: 3.59 OECD Test Guideline 107

octanol/water

**Auto-ignition temperature**Literature No test data available

**Decomposition temperature** No test data available

**Dynamic Viscosity** 50 mPa.s at 20 °C (68 °F) *Calculated.* 

Kinematic ViscosityNo test data availableExplosive propertiesNo data availableOxidizing propertiesNo data availableMolecular weightNo test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

### 10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

**Possibility of hazardous reactions:** Will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an aliphatic amine will cause irreversible polymerization with considerable heat build-up.

**Conditions to avoid:** Avoid short term exposures to temperatures above 300 °C Potentially violent decomposition can occur above 350 °C Avoid prolonged exposure to temperatures above 250 °C

Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid.

**Incompatible materials:** Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Avoid unintended contact with amines.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition. Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

## 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

## **Acute toxicity**

#### Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Page 6 of 11

LD50, Rat, female, > 2,000 mg/kg OECD Test Guideline 425 No deaths occurred at this concentration.

## **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402No deaths occurred at this concentration.

## Acute inhalation toxicity

Prolonged excessive exposure may cause adverse effects.

Maximum attainable concentration.

LC50, Rat, male and female, 4 Hour, dust/mist, > 3.4 mg/l No deaths occurred at this concentration.

### Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness.

## Serious eye damage/eye irritation

May cause eye irritation.

Corneal injury is unlikely.

#### Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

# **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

# **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

No relevant data found.

# Carcinogenicity

Product test data not available. Refer to component data.

## **Teratogenicity**

No relevant data found.

### Reproductive toxicity

No relevant data found.

#### Mutagenicity

In vitro genetic toxicity studies were negative in some cases and positive in other cases.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

### COMPONENTS INFLUENCING TOXICOLOGY:

Product name: D.E.R.\* 727 Epoxy Diluent Issue Date: 03/07/2016

## 4-tert-Butylphenyl glycidyl ether

Carcinogenicity

No relevant data found.

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

### **Toxicity**

#### Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 7.5 mg/l, OECD Test Guideline 203

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, static test, 48 Hour, 67.9 mg/l, OECD Test Guideline 202

# Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 9 mg/l, OECD Test Guideline 201

# Persistence and degradability

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 1.1 % **Exposure time:** 28 d

Method: OECD Test Guideline 301D

Theoretical Oxygen Demand: 2.56 mg/mg

### **Photodegradation**

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 0.316 d

Method: Estimated.

## Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or

Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.59 OECD Test Guideline 107

## Mobility in soil

Potential for mobility in soil is medium (Koc between 150 and 500).

Partition coefficient(Koc): 755 OECD 121: HPLC Method

Page 8 of 11

## 13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

## 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.(4-tert-Butylphenyl glycidyl ether)

UN number UN 3082

Class 9
Packing group ||||

Marine pollutant 4-tert-Butylphenyl glycidyl ether

Transport in bulk Consult IMO regulations before transporting ocean bulk

according to Annex I or II of MARPOL 73/78 and the

**IBC or IGC Code** 

Classification for AIR transport (IATA/ICAO):

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.(4-tert-

Butylphenyl glycidyl ether)

UN number UN 3082

Class 9
Packing group III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Page 9 of 11

## 15. REGULATORY INFORMATION

### **OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

## California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

## United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

# 16. OTHER INFORMATION

# **Hazard Rating System**

#### **NFPA**

Health	Fire	Reactivity
1	1	0

## Revision

Identification Number: 101224499 / A476 / Issue Date: 03/07/2016 / Version: 5.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

BLUE CUBE OPERATIONS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change

and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.