

Print this page Performance Additives

Additives

AddWorks® LXR™ 313

Edition Date February 28, 2019 Edition Number 4

Light stabilizers mixture for coatings

Product Description

AddWorks LXR 313 is a mixture of a triazine UV absorber with a low molecular weight hindered amine light stabilizer (HALS), designed for high performance stabilization of paints and clearcoats, and characterized by its broad compatibilities in both solventborne and waterborne coatings.

Benefits

A synergistic mixture of a triazine UV absorber with a hindered amine light stabilizer (HALS), designed for high performance stabilization of pigmented monocoat paints and clearcoats.

Physical Properties

Appearance	Yellow liquid	
Density (20°)	approx. 1,01 g/cm³	
Miscibility	Miscible with most of the commonly used organic solvents, e.g. n-butanol, ethyl acetate, xylene or white spirit, as well as with waterborne coatings (e.g. acrylics, 2K-PU) up to 3% addition on total resin solids.	

Applications

AddWorks LXR 313 can be recommended in all kind of high performance solventborne and waterborne coatings, for applications such as automotive clearcoats, plastic coatings and high end wood coatings. In acid-catalyzed solventborne coatings, where the basicity of the HALS component could inhibit crosslinking reaction with the binder, it is recommended to use the alternative mixture Hostavin TB-04.

Packaging & Handling

Delivery form

Liquid

Packaging

Steel drums 50 kg Pallet 300 kg (6 drums)

Storage

Storage below 10°C can cause a precipitate which can be removed by careful heating. Minimum shelf life is 2 years from the date of shipping when properly stored.

Safety

Hazards

Classification according CLP regulation (Regulation (EC) No. 1272/2008, as amended). Flammable liquids, Cat. 3
Skin irritation, Cat. 2
Chronic aquatic toxicity, Cat. 2
For further information please refer to the Material Safety Data Sheet.

Contact Us:

Please contact us for safety and regulatory details or the Material Safety Data Sheet (MSDS).

www.clariant.com





This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application.

- * Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.
- * For sales to customers located within the United States and Canada the following applies in addition: No express or implied warranty is made of the merchantability, suitability, fitness for a particular purpose or otherwise of any product or service.

© Trademark of Clariant registered in many countries. ® 2019 Clariant International Ltd