

SDS: 0018109

Date Prepared: 11/24/2019

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EBECRYL® 629 radiation curing resins

Synonyms: None

Product Description: Mixture of acrylated resin and acrylated monomer

Molecular Formula: Mixture Molecular Weight: Mixture

Intended/Recommended Use: Radiation curable coating ingredient

Uses advised against: This product should not be used in any application where unreacted liquid product

is intended to come in direct contact with skin or nails. Reason: sensitizing

properties.

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at http://www.allnex.com/contact

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC) See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ®, TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive Toxicant Hazard Category 2 Skin Corrosion / Irritation Hazard Category 2 Serious Eye Damage / Eye Irritation Hazard Category 2A Skin Sensitizer Hazard Category 1B Aquatic Environment Acute Hazard Category 1 Aquatic Environment Chronic Hazard Category 1

LABEL ELEMENTS



Signal Word WARNING

Hazard Statements

Suspected of damaging fertility or the unborn child

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Very toxic to aquatic life

Very toxic to aquatic life with long lasting effects

Precautionary Statements

Obtain special instructions before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

IF exposed or concerned: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

Specific treatment (see supplemental first aid instructions on this label).

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

SDS: 0018109

Date Prepared: 11/24/2019

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Collect spillage.

Store locked up.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification
Trimethylolpropane triacrylate	25 - 35	Skin Irrit. 2 (H315)
15625-89-5		Eye Irrit. 2A (H319)
		Skin Sens. 1B (H317)
		Aquatic Acute 1 (H400)
		Aquatic Chronic 1 (H410)
2-Hydroxyethyl methacrylate	5 - 10	Eye Irrit. 2A (H319)
868-77-9		Skin Sens. 1B (H317)
Acrylic acid	< 1.0	Flam. Liq. 3 (H226)
79-10-7		Acute Tox. 4 (H302)
		Acute Tox. 4 (H312)
		Acute Tox. 4 (H332)
		STOT Single 3 (H335)
		Skin Corr. 1A (H314)
		Eye Dam. 1 (H318)
		Aquatic Acute 1 (H400)
		Aquatic Chronic 2 (H411)
4-Methoxyphenol	0.2 - 0.35	Repr. 2 (H361d)
150-76-5		Acute Tox. 4 (H302)
		Skin Irrit. 3 (H316)
		Eye Irrit. 2A (H319)
		Skin Sens. 1B (H317)
		Aquatic Acute 2 (H401)
		Aquatic Chronic 3 (H412)
Acrylated resin	60 - 70	Skin Irrit. 2 (H315)
-		Eye Irrit. 2A (H319)

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

First-aid Measures

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

Skin Contact:

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Notes To Physician:

No specific measures have been identified.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media:

high pressure water jet.

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

Environmental Precautions:

Avoid release to the environment.

References to other sections:

See Sections 7, 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Avoid release to the environment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye/face protection.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

Storage Temperature: Store at 4 - 40 °C 39 - 104 °F

Reason: Quality.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

Eve Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing. Barrier creams may be used in conjunction with the gloves to provide additional skin protection.

Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

SDS: 0018109

Date Prepared: 11/24/2019

Gloves for short term exposure/splash protection - non exhaustive list:

Laminated multilayer gloves, break through time: > 60 min

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: < 60 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

Exposure Limit(s)

79-10-7 Acrylic acid

OSHA (PEL): Not established

ACGIH (TLV): (skin)

2 ppm (TWA)

Other Value: 1 ppm skin (Allnex)

150-76-5 4-Methoxyphenol

OSHA (PEL): Not established 5 mg/m³ (TWA) ACGIH (TLV): Other Value: Not established

Biological Exposure Limit(s)

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: clear to grey Appearance: liquid Odor: acrylate

> 100 °C 212 °F **Boiling Point: Melting Point:** Not available

Vapor Pressure: < 0.13 hPa @ 20 °C

Specific Gravity/Density: 1.18 g/cm³ Not available Vapor Density: Percent Volatile (% by wt.): Not available Not available Saturation In Air (% By Vol.): Not available **Evaporation Rate:** Not available Solubility In Water: Insoluble **Volatile Organic Content:**

Flash Point: > 100 °C 212 °F Setaflash Closed Cup

Not available

Flammable Limits (% By Vol): Not available **Autoignition Temperature:** Not available

Decomposition Temperature:

Partition coefficient

Not available Not available

(n-octanol/water):

Odor Threshold:
Viscosity (Kinematic):
Viscosity (Dynamic):

Explosive Properties:

Not available
Not available
Not available
Not available

SDS: 0018109

10. STABILITY AND REACTIVITY

Reactivity: No information available

Stability: Stable.

Conditions To Avoid: Keep away from heat, spark and flame. Avoid direct exposure to sunlight. Avoid

high temperatures. Loss of dissolved air. Loss of polymerization inhibitor.

Polymerization: May occur

Conditions To Avoid: Uncontrolled polymerization may cause rapid evolution of heat and increase in

pressure that could result in violent rupture of sealed storage vessels or containers Hazardous polymerization can occur when exposed to direct sunlight. Hazardous

exothermic polymerization can occur when heated.

Materials To Avoid: Avoid contact with peroxides.

Copper, copper alloys, carbon steel, iron and rust.

Contact with strong oxidizing agents. Avoid free radical producing initiators.

They give an exothermic reaction with the product.
Unintentional contact with them should be avoided.

Hazardous polymerization may occur.

Hazardous Decomposition

Products:

oxides of carbon

smoke

hvdrocarbons

soot

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

Acute toxicity - oral: Not Classified - Based on available data and/or professional judgment, the classification

criteria are not met.

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Acute toxicity - inhalation: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Skin corrosion / irritation: Causes skin irritation

Serious eye damage / eye irritation: Causes serious eye irritation

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Skin sensitization: May cause an allergic skin reaction

Carcinogenicity: Not Classified - Based on available data and/or professional judgment, the classification

SDS: 0018109

Date Prepared: 11/24/2019

criteria are not met.

Germ cell mutagenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Reproductive toxicity: Suspected of damaging fertility or the unborn child

Specific target organ toxicity (STOT) - single exposure: Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure: Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

Aspiration hazard: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

PRODUCT TOXICITY INFORMATION

ACUTE TOXICITY DATA

oral	rat	Acute LD50	> 2000 mg/kg
dermal	rabbit	Acute LD50	> 2000 mg/kg
inhalation	rat	Acute LC50 4 hr	> 5 mg/l (Dust/Mist)

LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation dermal Irritating
Acute Irritation eye Irritating

ALLERGIC SENSITIZATION

Sensitization Skin Sensitizing
Sensitization respiratory No data

GENOTOXICITY

Assays for Gene Mutations

Ames Salmonella Assay No data

OTHER INFORMATION

The product toxicity information above has been estimated.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

11. TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT TOXICITY DATA

Trimethylolpropane triacrylate has acute oral (rat) LD50 and acute dermal (rabbit) LD50 values of 3680 mg/kg and 5170 mg/kg, respectively. No mortality was observed in two inhalation studies. Direct contact with this material may cause eye and skin irritation. Repeated or prolonged skin contact may cause allergic skin reactions. Results of in vitro mutagenicity testing for trimethylolpropane triacrylate are mixed with both positive and negative findings. Trimethylolpropane triacrylate may cause mutagenic effects based on in vitro studies. However, a more definitive in vivo study indicates trimethylolpropane triacrylate is not mutagenic (non-genotoxic). This was again confirmed in a COMET assay. In a long-term bioassay in which trimethylolpropane triacrylate was applied dermally to mice, trimethylolpropane triacrylate induced some tumour formation at the side of application only. These findings have been related to excessive local irritation, with no systemic carcinogenic potential. No developmental toxicity nor fertility impairment has been observed.

Hydroxyethyl methacrylate (CAS # 868-77-9) has acute oral (rat) and dermal (rabbit) LD50 values of > 5000 mg/kg and > 3000 mg/kg, respectively. This material may cause moderate eye and mild skin irritation. Repeated skin contact with hydroxyethyl methacrylate may cause skin sensitization (guinea pig). Cases of sensitisation also observed in humans. No indications of teratogenic effects in experimental animals. The substance was not mutagenic in the Ames test.

Acrylic acid has acute oral (rat) LD50, acute dermal (rabbit) LD50, and acute inhalation (rat, 4-hr, vapor) LC50 values of 617-1405 mg/kg, >2000 mg/kg, and >1730 ppm (>5.1 mg/L), respectively. Direct contact may cause severe eye irritation with corneal injury which may result in permanent impairment of vision and even blindness. Chemical burns may occur. Vapors may also cause severe eye irritation. Skin contact may cause severe skin burns. Symptoms may include pain, severe local redness, swelling, blistering and tissue damage. Inhalation overexposure may cause severe irritation of the respiratory tract. Repeated overexposures may have effects on the kidney. Acrylic acid did not cause cancer when given to rats in their drinking water throughout their lifetime. No skin tumors occurred in mice receiving repeated skin applications of acrylic acid at nonirritating doses. A slight, not statistically significant increase in skin tumors reported in another study is difficult to interpret due to the low incidence and conflicting information regarding dose. This substance has been toxic to the fetus in laboratory animals at doses toxic to the mother but has not been found to cause birth defects in laboratory animals. In laboratory animal studies with acrylic acid, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. The results of in vitro genetic toxicity studies are predominantly negative. Animal genetic toxicity studies are negative (not mutagenic).

4-Methoxyphenol has an oral LD50 of 1630 mg/Kg (rat), and a dermal LD50 of > 2000 mg/Kg (rat). Suspect skin sensitizer (guinea pig). 4-Methoxyphenol is a moderate to severe eye irritant and a slight skin irritant. Ingestion causes gastrointestinal irritation with nausea and vomiting and possibly ulceration. Overexposure (ingestion/inhalation) can cause methemoglobinemia with cyanosis, as well as central nervous system (CNS) depression, with symptoms ranging from headache, and confusion, to coma, and respiratory failure.
4-Methoxyphenol may be absorbed through skin, causing symptoms similar to ingestion/inhalation exposure routes. In vitro testing hasn't revealed genotoxic effects. This was confirmed by an in vivo clastogenicity study. No increase in tumour incidence was observed in several carcinogenicity assays. 4-Methoxyphenol has induced teratogenic effects in oral (gavage) prenatal toxicity studies.

The toxicological properties of acrylated resin have not been fully investigated. Direct contact with this material may cause moderate eye and skin irritation.

Carcinogenicity

This product contains one or more Carcinogen Chemical(s) in accordance with IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), ACGIH (American Conference of Governmental Industrial Hygienists).

Component / CAS No.	Carcinogen
Trimethylolpropane triacrylate	IARC 2B
15625-89-5	



WARNING: Reproductive Harm – www.P65Warnings.ca.gov

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

Overall Environmental Toxicity: Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Trimethylolpropane triacrylate (15625-89-5)	LC50 = 0.87 mg/L - Brachydanio rerio - 96hrs
2-Hydroxyethyl methacrylate (868-77-9)	LC50 213 - 242 mg/L - Pimephales promelas (96h) LC50 = 227 mg/L - Pimephales promelas (96h)
Acrylic acid (79-10-7)	LC50 = 222 mg/L - Brachydanio rerio (96h)
4-Methoxyphenol (150-76-5)	LC50 = 28.5 mg/L - Oncorhynchus mykiss (96hrs) LC50 = 84.3 mg/L - Pimephales promelas (96hrs)
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Water Flea
Trimethylolpropane triacrylate (15625-89-5)	EC50 = 19.9 mg/L - Daphnia magna - 48hrs
2-Hydroxyethyl methacrylate (868-77-9)	Not available
Acrylic acid (79-10-7)	LC50 = 270 mg/L - Daphnia magna (24h) EC50 = 95 mg/L - Daphnia magna (48h)
4-Methoxyphenol (150-76-5)	EC50 = 3 mg/L - Daphnia magna (48hrs) NOEC = 1.32 mg/L - Daphnia magna (48hrs)
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Algae
Trimethylolpropane triacrylate (15625-89-5)	EC50 = 18.8 mg/L - Scenedesmus subspicatus - 72hrs EC10 = 1.9 mg/L - Scenedesmus subspicatus - 72hrs
2-Hydroxyethyl methacrylate (868-77-9)	Not available
Acrylic acid (79-10-7)	EC50 = 0.04 mg/L - Desmodesmus subspicatus (72h) EC50 = 0.17 mg/L - Pseudokirchneriella subcapitata (96h)
4-Methoxyphenol (150-76-5)	EC50 = 54.7 mg/L - Pseudokirchnerella subcapitata (72hrs)
Acrylated resin (-)	Not available

Component / CAS No.	Partition coefficient
Trimethylolpropane triacrylate (15625-89-5)	Log Kow = 4.35
2-Hydroxyethyl methacrylate (868-77-9)	0.47
Acrylic acid (79-10-7)	0.38 - 0.46
4-Methoxyphenol (150-76-5)	log Kow = 1.3
Acrylated resin (-)	Not available

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seg) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9
Packing Group: III
UN/ID Number: UN3082

Transport Label Required: Miscellaneous

Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIMETHYLOLPROPANE TRIACRYLATE

Comments: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to

non-bulk packagings transported by motor vehicles, rail cars or aircraft.

TRANSPORT CANADA

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9 Packing Group: III UN Number: UN3082

Transport Label Required: Miscellaneous

Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIMETHYLOLPROPANE TRIACRYLATE

ICAO / IATA

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9

Packing Group: III UN Number: UN3082

Transport Label Required: Miscellaneous

TECHNICAL NAME (N.O.S.): TRIMETHYLOLPROPANE TRIACRYLATE

IMO

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9 UN Number: UN3082 Packing Group: III

Transport Label Required: Miscellaneous Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIMETHYLOLPROPANE TRIACRYLATE

SPECIAL PRECAUTIONS FOR USER

Protect against external heat sources above +40°C/104°F.

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

Canada: One or more components of this product are NOT included on the Canadian Domestic Substances List (DSL). These components are included on the Canadian Non-Domestic Substances List (NDSL).

European Economic Area (including EU): When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

New Zealand: This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

Philippines: All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

Taiwan: All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

Physical Hazards

Not applicable

Health Hazards

Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sensitization Serious eye damage or eye irritation

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons For Issue: Revised Section 3

Revised Section 11

Date Prepared: 11/24/2019
Date of last significant revision: 10/12/2018

Component - Hazard Statements

Trimethylolpropane triacrylate

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

2-Hydroxyethyl methacrylate

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Acrylic acid

H226 - Flammable liquid and vapor.

H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

H400 - Very toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

H302 - Harmful if swallowed.

H316 - Causes mild skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H361d - Suspected of damaging the unborn child.

H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Acrylated resin

4-Methoxyphenol

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Emergency phone numbers for other regions

Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia)

China (PRC): +86(0)25 8547 7110 (Jiangsu registration center) / +86(0)532 8388 9090 (NRCC)

SDS: 0018109

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24) Japan: +81 345 789 341 (Carechem 24) Korea: +82 2 3479 8401 (Carechem 24) Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24) Taiwan: +886 2 8793 3212 (Carechem 24) Vietnam: +84 8 4458 2388 (Carechem 24) All Others: +65 3158 1074 (Carechem 24)

Europe

+44 (0) 1235 239 670 (Carechem 24)

Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

Prepared By: Product Stewardship & Regulatory Affairs Department, http://www.allnex.com/contact

Date Prepared: 11/24/2019

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.