

HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: HYBASE ® C500

Product Use Description: Additive

Synonyms: calcium sulfonate detergent

Company: LANXESS Solutions US Inc.

2 Armstrong Road Shelton, Ct

06484

United States of America (USA)

Telephone: (US) +1 866-430-2775

Emergency telephone

number:

CHEMTREC: (24 hours) 800-424-9300

: US: 800-292-5898 (Technical inquiries)

For additional emergency telephone numbers see section 16 of the Safety

Data Sheet.

Prepared by <u>Product Safety Department</u>

(US) +1 866-430-2775

MSDSRequest@lanxess.com

Recommended use of the chemical and restrictions on use

Recommended use : Additive

Restrictions on use : Restricted to professional users.

SECTION 2. HAZARDS IDENTIFICATION

Form	viscous liquid
Colour	brown
Odour	mild hydrocarbon-like

GHS Classification

Eye irritation : Category 2A

GHS label elements



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Signal word : Warning

Hazard pictograms

 $\langle ! \rangle$

Hazard statements : H319 Causes serious eye irritation.

Other hazards None

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
calcium carbonate	471-34-1	>= 30 - < 50 %
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	>= 30 - < 50 %
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	>= 10 - < 20 %
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 5 - < 10 %
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	>= 1 - < 5 %
calcium dihydroxide	1305-62-0	>= 1 - < 2.5 %



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

SECTION 4. FIRST AID MEASURES

If inhaled : Remove to fresh air.

Aspiration may cause pulmonary oedema and pneumonitis.

If breathing is difficult, give oxygen. If symptoms persist, call a physician.

In case of skin contact : Wash off with warm water and soap.

If skin irritation persists, call a physician. Wash contaminated clothing before re-use.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

Get medical attention if irritation develops and persists.

If swallowed : Do NOT induce vomiting.

Rinse mouth with water. Obtain medical attention.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delaved

Notes to physician

: irritant effects

: For specialist advice physicians should contact the Poisons

Information Service.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : (on small fires)

Carbon dioxide (CO2)

Dry chemical Dry sand

Extinguishing media - large fires

Foam Water mist

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not use a solid water stream as it may scatter and spread

fire

Burning produces irritant fumes.

Exposure to decomposition products may be a hazard to

health.

Specific extinguishing : Cool containers/tanks with water spray.

SAP 6.0 SDS 2012-2 NA GHS 3 / 13 SDS Number: 400000004380



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

methods

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation.

Use non-slip safety shoes in areas where spills or leaks can

occur.

Wear suitable protective equipment.

Environmental precautions : Should not be released into the environment.

Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

: Clean-up methods - small spillage Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean-up methods - large spillage Dam up. Large spills should be collected mechanically (remove by

pumping) for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Handle and open container with care.

Keep away from heat and sources of ignition.

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Use personal protective equipment as required.

Wash thoroughly after handling.

Keep container closed when not in use.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-

ventilated place.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAP 6.0 SDS 2012-2 NA GHS 4 / 13 SDS Number: 400000004380



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent- refined heavy paraffinic	64741-88-4	TWA	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		PEL (particulate)	5 mg/m3	CAL PEL
calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
		TWA	5 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL

Engineering measures : Ensure that extracted air cannot be returned to the workplace

through the ventilation system.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Respirator with combination filter for vapour/particulate (EN

141)

Hand protection

Remarks : Impervious gloves Replace when worn.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Impervious clothing



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection. When using do not eat, drink or smoke.

Wash thoroughly after handling. Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : brown

Odor : mild hydrocarbon-like
Odour Threshold : No data available
pH : No data available

:

Not applicable

Boiling point/boiling range : No data available

Flash point : > 180 °C

Method: open cup

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.0008 hPa (20 °C)

Relative vapour density : No data available

Relative density : > 1 (25 °C)

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Description: partly soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Viscosity

Viscosity, kinematic : > 30 mm2/s (40 °C)

SAP 6.0 SDS 2012-2 NA GHS 6 / 13 SDS Number: 400000004380



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Exposure to moisture Contamination

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

Metal oxides

Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

calcium carbonate:

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

Sulfonic acids, petroleum, calcium salts:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

SAP 6.0 SDS 2012-2 NA GHS 7 / 13 SDS Number: 400000004380



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Method: OECD Test Guideline 401

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 4,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

calcium dihydroxide:

Acute oral toxicity : LD50 (Rat): 7,340 mg/kg

Skin corrosion/irritation

Components:

calcium carbonate:

Species: Rabbit

Result: No skin irritation

calcium dihydroxide: Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

calcium carbonate:

Species: Rabbit

Result: No eye irritation

calcium dihydroxide:

Species: Rabbit

Result: Risk of serious damage to eyes.

Method: Draize Test

Respiratory or skin sensitisation

Product:

Result: Does not cause skin sensitisation.

Components:

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Result: Probability or evidence of low to moderate skin sensitisation rate in humans

Sulfonic acids, petroleum, calcium salts:

Result: Probability or evidence of low to moderate skin sensitisation rate in humans

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Result: Probability or evidence of low to moderate skin sensitisation rate in humans

calcium dihydroxide:

Assessment: Did not cause sensitisation on laboratory animals.



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

calcium carbonate: Effects on fertility

Species: Rat

Application Route: Oral

Reproductive toxicity -

Assessment

: No toxicity to reproduction No effects on or via lactation

STOT - single exposure

Components:

calcium dihydroxide:

Assessment: May cause respiratory irritation.

Aspiration toxicity

Product:

No aspiration toxicity classification

Further information

Product:

Remarks: No data is available on the product itself.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Components:

Sulfonic acids, petroleum, calcium salts:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): >

10,000 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : EbC50 (Green algae (Scenedesmus subspicatus)): > 100 mg/l

Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 201

GLP: yes

ErC50 (Green algae (Scenedesmus subspicatus)): > 100 mg/l

Exposure time: Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 201

GLP: yes

calcium dihydroxide:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 160 mg/l

Exposure time: 96 h Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

Product:

Biodegradability : Result: No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 8.6 %

 $SAP 6.0 SDS 2012-2 NA GHS \qquad \qquad 10 \ / \ 13 \qquad \qquad SDS Number: \ 400000004380$



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Exposure time: 28 d

GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

Product:

Mobility : Remarks: No data available

Other adverse effects

Product:

Results of PBT and vPvB

assessment

: This mixture contains no substance considered to be

persistent, bioaccumulating and toxic (PBT).

Additional ecological

information

No information on ecology is available. Avoid release to the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of wastes in an approved waste disposal facility.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR



HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

Not regulated as a dangerous good

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

California Prop. 65

WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

The components of this product are reported in the following inventories:

All components of this product are on the Canadian DSL

AICS
On the inventory, or in compliance with the inventory

NZIOC
On the inventory, or in compliance with the inventory

ENCS
On the inventory, or in compliance with the inventory





HYBASE ® C500

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019

KECI On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory **PICCS IECSC** On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory **TCSI US.TSCA**

On TSCA Inventory

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
Mexico:		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.