

## D.E.R.™ 322

Please use this Technical Data Sheet (TDS) in conjunction with this product's country-specific Safety Data Sheet (SDS) and the Safe Use conditions as described therein. Current Safety Data Sheets can be requested from Olin at info@olinbc.com

**Description** D.E.R.<sup>™</sup> 322 Liquid Epoxy Resin is a reaction product of epichlorohydrin and bisphenol A modified with an aromatic mono-functional reactive diluent.

D.E.R. 322 Liquid Epoxy Resin is diluted standard bisphenol A based liquid epoxy resin of low viscosity. The low viscosity is advantageous in compositions containing large amounts of filler. D.E.R. 322 Resin has a cure rate similar to unmodified bisphenol A based liquid epoxy resins.

The reactive diluent contained in D.E.R. 322 Epoxy Resin limits somewhat the solvent resistance, however, an improved acid resistance can be observed using D.E.R. 322 Epoxy Resin instead of D.E.R. 331 Liquid Epoxy Resin. D.E.R. 322 Liquid Epoxy Resin exhibits a very low tendency to crystallize.

D.E.R. 322 Epoxy Resin can be hot or cold cured by blending with polyamine, polyamide and modified versions of these. Elevated temperature cures are necessary and post-cures required to develop full end properties if anhydride or catalytic curing agents are employed.

## Applications • Adhesives

- Building & Civil Engineering
- Castings / Potting / Encapsulation / Tooling
- · Composites
- Industrial Coatings: Marine and Protective

| Properties                        | Nominal Value | (English) | Nominal Value | (SI)  | Test Method |
|-----------------------------------|---------------|-----------|---------------|-------|-------------|
| EEW                               | 183 to 193    | g/eq      | 183 to 193    | g/eq  | ASTM D1652  |
| Viscosity, absolute (77°F (25°C)) | 5500 to 8500  | mPa·s     | 5500 to 8500  | mPa·s | ASTM D445   |
| Density (77°F (25°C))             | 1.15          | g/cm³     | 1.15          | g/cm³ | ASTM D4052  |

## Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

<sup>1</sup> Typical properties: these are not to be construed as specifications.

| Product<br>Stewardship         | Olin Corporation has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis of our Product Stewardship philosophy by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee and public health and the environment.<br>Olin encourages its customers and potential users of Olin products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that Olin products are not used in ways for which they were not intended or tested, Olin personnel are available to assist customers in dealing with ecological and product safety considerations. Your Olin sales representative car arrange for the proper contacts.   |                              |              |                |  |  |  |
|--------------------------------|---|------------------------------|--------------|----------------|--|--|--|
|                                |   |                              |              |                |  |  |  |
| Regulatory<br>Datasheets (RDS) | Olin Corporation provides information on the regulatory status of its products under prominent regulatory programs in the Regulatory Datasheet (RDS). Regulatory Datasheets can be requested from Olin at info@olinbc.com   |                              |              |                |  |  |  |
| Disclaimer                     | Notice: No freedom from any patent or other intellectual property rights owned by Olin or others is to be inferred. Olin assumes no obligation or liability for the information in this document. The information provided herein is presented in good faith and is based on the best of Olin's knowledge, information, and belief. Since use conditions at non-Olin facilities are beyond Olin's control and government requirements may differ from one location to another and may change with time, it is solely the Buyer's responsibility to determine whether Olin's products are appropriate for the Buyer's use, and to assure the Buyer's workplace, use, and disposal practices are in compliance with applicable government requirements. Consequently, Olin assumes no obligation or liability for use of these materials and makes no warranty, express or implied. The user of the information provided is solely responsible for compliance with any applicable government requirements. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. |                              |              |                |  |  |  |
| Contact                        | USA:  | 1-844-238-3445               | Canada:      | 1-877-304-4442 |  |  |  |
| Information                    | China:  | 86-4008859485                | France:      | 33-176361145   |  |  |  |
|                                | Germany:  | 49-41417693000               | Hong Kong:   | 852-58081886   |  |  |  |
|                                | Italy:  | 39-0694805761                | Japan:       | 81-345406770   |  |  |  |
|                                | Latin America:  | 55-1151884105                | Russia:      | 7-4996092327   |  |  |  |
|                                | Singapore:<br>United Kingdom:   | 65-31632006<br>44-8000869047 | South Korea: | 82-260221296   |  |  |  |
| www.OlinEpoxy.com              |   |                              |              |                |  |  |  |

www.OlinEpoxy.com

