

## Polycin® GR-50 Technical Data Sheet

## Product Identification

Polycin<sup>®</sup> GR-50 is a 100% solids, castor oil-based derivative designed for use as a primary polyol or reactive diluent in polyurethane sealants and adhesives systems. Polycin<sup>®</sup> GR-50 imparts low hardness and provides VOC reduction while offering the beneficial properties of castor oil derivatives, such as improved flow and levelling.

Physical
<b>Properties</b>

<u>Property</u>	<u>Typical Value</u>
Acid Value	2
Appearance	clear amber liquid
Color, Gardner	5
Density, lbs./gal, 25°C	7.87
Equivalent Weight	1085
Functionality	2.2
Hydroxyl Value	52
Moisture, %	0.04
Specific Gravity, 25°C/25°C	0.943
Viscosity, cP @ 25°C	1,400
Renewable Content, %	100

## **Applications**

- Formulation of 100% solids polyurethanes
- Moisture resistance
- VOC reduction in adhesives and sealants
- Urethane Intermediates, Prepolymers

For toxicity or regulatory information please consult the Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA

USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com

Web: www.vertellus.com