

## D.E.H.™ 805

Please use this Technical Data Sheet (TDS) in conjunction with this product's country-specific Safety Data Sheet (SDS) and the Safe Use conditions as described therein. Current Safety Data Sheets can be requested from Olin at info@olinbc.com

#### **Description**

D.E.H.<sup>TM</sup> 805 is an amine curing agent dissolved in water and designed to emulsify epoxy resins. The product contains no VOC according to the European Directive 2004/42/EC and no alkyl phenol.

#### **Benefits**

D.E.H. 805 serves as a curing agent for thin layer applications (primer or top-coat). When cured with D.E.R.™ 3221 and applied as a primer under a D.E.H. 804 based top-coat, D.E.H. 805 did not contribute to significant emissions, such that the full flooring system could pass the AgBB evaluation scheme and get labeled A+ according to the French labeling of construction products evaluation scheme. When using D.E.H. 805 to develop formulations applicable with a roller, flooring presenting a matte, satin or high gloss finish can be achieved.

### **Applications**

- Building & Civil Engineering: Primers & Impregnation
- Building & Civil Engineering: Roller Coating Flooring

Properties	Nominal Value	(English)	Nominal Value	(SI)	<b>Test Method</b>
AHEW	220	g/eq	220	g/eq	
Viscosity, absolute (77°F (25°C), C/P 50 mm)	10000 to 19000	mPa⋅s	10000 to 19000	mPa⋅s	ISO 3219
Colour (Max. Gardner)	6		6		ASTM D1544
Density (77°F (25°C))	1.11	g/cm³	1.11	g/cm³	ASTM D4052
Solids Content	64 to 66	%	64 to 66	%	ASTM D2369
Amine Value	170 to 230	mg KOH/g	170 to 230	mg KOH/g	ISO 9702
Pot Life <sup>2</sup> (73°F (23°C), 100 g)	120	min	120	min	GELNORM Geltimer-TC
Pendulum Hardness (Koenig) <sup>3</sup>					DIN 53157
55°F (13°C), 80% RH, 1.0 day	6		6		
55°F (13°C), 80% RH, 2.0 day	16		16		
55°F (13°C), 80% RH, 7.0 day	54		54		
73°F (23°C), 50% RH, 1.0 day	34		34		
73°F (23°C), 50% RH, 2.0 day	53		53		
73°F (23°C), 50% RH, 7.0 day	124		124		
Compressive Strength <sup>4</sup>					ISO 604
14.0 day, 73°F (23°C), 50% RH	3480	psi	24.0	MPa	

#### Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> Reference Resin: D.E.R.™ 331

<sup>&</sup>lt;sup>3</sup> Reference Resin: D.E.R.™ 3221

<sup>&</sup>lt;sup>4</sup> Reference Resin: D.E.R.™ 3531

## Product Stewardship

Olin Corporation has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis of our Product Stewardship philosophy by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee and public health and the environment.

Olin encourages its customers and potential users of Olin products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that Olin products are not used in ways for which they were not intended or tested, Olin personnel are available to assist customers in dealing with ecological and product safety considerations. Your Olin sales representative can arrange for the proper contacts.

# Regulatory Datasheets (RDS)

Olin Corporation provides information on the regulatory status of its products under prominent regulatory programs in the Regulatory Datasheet (RDS). Regulatory Datasheets can be requested from Olin at info@olinbc.com

#### Disclaimer

Notice: No freedom from any patent or other intellectual property rights owned by Olin or others is to be inferred. Olin assumes no obligation or liability for the information in this document. The information provided herein is presented in good faith and is based on the best of Olin's knowledge, information, and belief. Since use conditions at non-Olin facilities are beyond Olin's control and government requirements may differ from one location to another and may change with time, it is solely the Buyer's responsibility to determine whether Olin's products are appropriate for the Buyer's use, and to assure the Buyer's workplace, use, and disposal practices are in compliance with applicable government requirements. Consequently, Olin assumes no obligation or liability for use of these materials and makes no warranty, express or implied. The user of the information provided is solely responsible for compliance with any applicable government requirements. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

## Contact Information

USA: 1-844-238-3445 1-877-304-4442 Canada: China: 86-4008859485 France: 33-176361145 Germany: 49-41417693000 Hong Kong: 852-58081886 81-345406770 39-0694805761 Italy: Japan: Latin America: 55-1151884105 Russia: 7-4996092327 Singapore: 65-31632006 South Korea: 82-260221296 United Kingdom: 44-8000869047

www.OlinEpoxy.com

