



SALES SPECIFICATION

Product name: D.E.R.® 664 Epoxy Resin

Characteristics	Min	Max	Unit	Method	Test Frequency	Note
Epoxide Eq. Wt.	875	955		ASTM D1652		
Solution Viscosity @ 25degC	500	900	cSt	ASTM D445		0002
Softening Point	100.0	110.0	°C	ASTM D3104		
Color, Pt-Co in solution		100		ASTM D1209		0004

Characteristic Notes:

*** Determined on 40% non-volatiles in Diethylene Glycol Monobutyl Ether.

*** Determined on 40% Non-volatiles in Diethylene Glycol Monobutyl Ether.

Additional Quality Requirements

Additional Product Information

A medium molecular weight Bisphenol A type solid epoxy resin

General Notes

Packaging & Labelling:

Unless otherwise specified this product is supplied in 25 Kg bags.

Minimum container markings will include:

- Product Name
- Batch Number
- Net Weight
- Appropriate hazard warning information

®TM*TRADEMARK OF OLIN CORPORATION (OLIN) OR AN AFFILIATED COMPANY OF OLIN

Olin Document Information

Specification Number	QAC Number	Effective Date	Supersedes Date	Print Date
19346	100	2016-09-06	2010-05-04	2023-11-14