

Product information

VPS 4721

Epoxy functional silane resin

Technical data

Properties and test methods	Value	Unit	Method
Flash point	> 95	°C	DIN EN ISO 2719
Viscosity (20 °C)	700-1200	mPa's / cSt	DIN 53015

Registrations

VPS 4721

on request	

VPS 4721 is a bifunctional organosilane possessing a reactive organic epoxide and hydrolyzable inorganic methoxysilyl groups.

The dual nature of its reactivity allows VPS 4721 to bind chemically to both inorganic materials (e.g. glass, metals, fillers) and organic polymers (e.g. thermosets, thermoplastics, elastomers), thus functioning as an adhesion promoter, crosslinking agent and/or surface modifier.

VPS 4721 is a colorless liquid. It is soluble in alcohols, ketones and aliphatic or aromatic hydrocarbons.

Safety and handling

Before considering the use of VPS 4721 please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website www.dynasylan.com or upon request from your local representative, customer service or from Evonik Resource Efficiency GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging, storage and shelf life

VPS 4721 is supplied in 25 kg, 210 kg drums and 1.000 kg bulk containers.

In the unopened container VPS 4721 has a shelf life of min. 12 months from delivery.

Please do not store above 35°C or in the direct sunlight.

Properties and applications

VPS 4721 is a <u>novel ingredient</u> for special formulations and can be used in many applications in <u>different industries</u>. Examples are:

- glass fiber/glass fabric composites: as a finish or a size ingredient
- foundry resins: as an additive to polyurethane resins
- sealants and adhesives: as a primer or additive
- mineral filled composites: for pretreatment of fillers and pigments or as an additive to the polymer
- paints and coatings: as an additive and as a primer for improving adhesion to the substrate, especially glass and metal
- as an additive for polymer dispersions

Important product effects that can be achieved through the use of VPS 4721 as an additive include:

- improved mechanical properties, such as flexural strength, tensile strength, impact strength and modulus of elasticity
- improved moisture and corrosion resistance
- improved electrical properties, for example dielectric constant, volume resistivity
- better adhesion on substrates
- crosslinking of suitable polymers and polymer dispersions
- imporved storage stability of formulations

VPS 4721 can be used for

- filler dispersions
- viscosity reduction
- increased filler loading
- non yellowing

Reactivity

In the presence of water, the methoxy groups of VPS 4721 hydrolyze to form reactive silanol groups which can bond to a variety of inorganic substrates. The organophilic glycidyl end of VPS 4721 can react with a suitable polymer. Hydrolysis of VPS 4721 can be catalyzed by organic acids such as acetic acid. Examples of suitable inorganic substrates are glass, glass fibers, quartz, cristobalite and metals.

VPS 4721 may be used in epoxy resins, phenolic resins, polyurethanes, PVAC, acrylates, polysulfides.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe/Middle-East/Africa/RoW Evonik Resource Efficiency GmbH

Business Line Silanes Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59 13636 FAX +49 6181 59 713915 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik (SEA) Pte. Ltd.

Business Line Silanes
3 Internatioanl Business Park
#07-18, Nordic European Centre
Singapore 609927
PHONE +65 6809 6576
FAX +65 6809 6699
dynasylan@evonik.com
www.dynasylan.com

Asia / Pacific Evonik Japan Co. Ltd

Business Line Silanes
12th Floor Monolith Building
2-3-1, Nishi-Shinjuku-ku
Tokyo 163-0912
Japan
PHONE +81 353 23 7446
FAX +81 353 23 7397
dynasylan@evonik.com
www.dynasylan.com

North America Evonik Corporation

Business Line Silanes
299 Jefferson Road
Parsippany, NJ 07054-0677
USA
PHONE (TOLL FREE) +1 800 237 67 45
PHONE +1 973 929 8513
FAX +1 973 929 8503
dynasylan@evonik.com
www.dynasylan.com

Asia / Pacific Evonik Specialty Chemicals (Shanghai) Co. Ltd.

Business Line Silanes
55, Chungdong Road
Xinzhuang Industry Park
Shanghai 201108
P.R. China
PHONE +86 21 61191-399
FAX +86 21 61191-648
dynasylan@evonik.com
www.dynasylan.com

Asia / Pacific Evonik India Pvt. Ltd.

Business Line Silanes
Krislon House
Saki Vihar Road, Anderi (E)
Mumbai - 400 072
India
PHONE +91 226 7238 809
FAX +91 226 7238 811
dynasylan@evonik.com
www.dynasylan.com

North America Silbond Corporation

9901 Sand Creek Highway Weston, MI 49289 USA PHONE +1 517 436 9316 FAX +1 517 436 3148 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Korea Ltd.

Business Line Silanes 94, Galsan 1-dong Bupyeong-gu Incheon, 403-081 Korea PHONE +82 2320 4773 FAX +82 2783 2520 dynasylan@evonik.com www.dynasylan.com

Latin America Evonik Brasil Ltda.

Business Line Silanes
Alameda Campinas, 579
01404-000 São Paulo-SP
Brazil
PHONE +55 11 3146 4123
FAX +55 11 3146 4148
dynasylan@evonik.com
www.dynasylan.com

Asia / Pacific Evonik Taiwan Ltd.

Business Line Silanes
Artist Construction Bldg.
9F, No. 133
Min Sheng East Road, Sec 3
Taipei, 105 Taiwan, R.O.C.
Taiwan 10596
PHONE +886 227 17 1242
FAX +886 227 17 2106
dynasylan@evonik.com
www.dynasylan.com

