



Print this page **Advanced Surface Solutions**

Additives

Ceridust® 3715

Edition Date April 14, 2015 **Edition Number** 9

Modified polyethylene wax

Product Description

Ceridust 3715 is a micronized, polar modified polyethylene wax recommended for solvent and water based coatings and inks

Benefits

- Superior matting properties
- Excellent scratch resistance and slip properties
- Excellent rub resistance and gloss reducing properties when used in printing inks

Specifications

Delivery Specifications and (*) General Properties

Characteristics	Unit	Target value	Test method
Appearance		white micronized powder	QM-AA-634
Acid value	[mg KOH/g]	2,0 - 5,0	ISO 2114
Drop point	[°C]	122 - 127	ISO 2176
Particle size d50	[µm]	7,5 - 9,5	QM-AA-112
*Density (23°C)	[g/cm³]	~ 0,97	ISO 1183

Applications

Ceridust 3715 is recommended for solvent and water based coatings and inks.

It is an excellent rub and scratch resistance additive for all kind of printing inks. The fine powder is easy to disperse especially in water based printing inks. Due to its chemical characteristic it is very stable in water based formulations.

In solvent and water based coatings the micronized polyethylene creates an excellent scratch resistance. The strong matting effect makes the Ceridust 3715 to a very effective matting agent. Also the slip performance can be influenced by the Ceridust 3715.

Packaging and Handling

Delivery form

Micronized powder

Packaging

Paper bag 20 kg
Pallet 600 kg (30 bags)

Storage

For best shelf life store this product in a dry area at normal ambient temperatures.
Minimum shelf life is 2 years from the date of shipping when properly stored.

Safety

Hazards

The product does not require a hazard warning label according CLP regulation (Regulation (EC) No. 1272/2008, as amended).
For further information please refer to the Material Safety Data Sheet.

Contact Us;

Please contact us for safety and regulatory details or the Material Safety Data Sheet (MSDS).

www.clariant.com



Clariant International Ltd



This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application.

* Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

* For sales to customers located within the United States and Canada the following applies in addition: No express or implied warranty is made of the merchantability, suitability, fitness for a particular purpose or otherwise of any product or service.

© Trademark of Clariant registered in many countries.

© 2019 Clariant International Ltd