



# PRODUCT DATA SHEET

## PURETOL™ 19

TEST DESCRIPTION	METHOD	SPECIFICATIONS		TYPICAL
Product Code				PTL19
Relative Density at 20 °C	ASTM D4052	0.845	0.905	0.861
Kinematic Viscosity, cSt at 40 °C	ASTM D445	34.9	37.2	36.1
Kinematic Viscosity, cSt at 100 °C	ASTM D445		Report	5.86
Saybolt Universal Viscosity at 100 °F	ASTM D2161		Report	186
Appearance, Visual	LORM 004		Clear & Bright	Clear & Bright
Colour, Saybolt	ASTM D156	30		+30
Pour Point, °C	ASTM D5950		Report	-15
Flashpoint, C O C, °C	ASTM D92		Report	220
* Exp. Date, from Date of Manufacture*	3 YEARS		Pass	Pass
Readily Carbonizable Substances Test	USP/NF Curr Rev		Pass	Pass
Limit of Sulfur Compounds	USP/NF Curr Rev		Pass	Pass
Solid Paraffin	USP/NF Curr Rev		Pass	Pass
Limit of Polycyclic Aromatic Hydrocarbon	USP/NF Curr Rev		Pass	Pass
Acidity	USP/NF Curr Rev		Pass	Pass
Infrared Absorption	USP/NF Curr Rev		Pass	Pass

Date Issued: 7/31/2018

Date Reviewed: 7/14/2022

### PURETOL™ 19 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA) 21 CFR 172.878 White Mineral Oil and 21 CFR 178.3620(a) Mineral Oil
- Meets United States Pharmacopoeia (USP) Mineral Oil Monograph
- Certified Kosher (Passover)
- Certified Halal
- Certified Vegan
- Expiry Date, from Date of Manufacture is 3 years

**Petro-Canada Lubricants Inc.**

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

[lubricants.petro-canada.com](http://lubricants.petro-canada.com)