

WayncorTM 222 – Corrosion Inhibitive Pigment.

Description – Zinc Phosphate

WayncorTM 222 is a white, non-refractive, anti-corrosive pigment used in protective coatings. It is widely considered by the coatings industry to be a standard corrosion inhibitor. It exhibits a high degree of versatility and is compatible with almost all commercially available aqueous and solvent based coatings. The use level will vary depending upon resin system, pigment volume concentration and desired performance parameters, however typical use levels are between 3 – 10% total formula weight.

Characteristic	Test Method	Typical Value
Appearance		White powder
Zinc as ZnO [%]		63 - 65
Phosphate as P ₂ O ₅ [%]		35 - 37
Specific Gravity	ASTM D-153	3.25
Bulking Value [gal/lb]		0.036
[1/kg]		0.308
рН	ASTM	5.5 - 8.0
	D-1208	
Conductivity [micro Siemens]	ASTM	< 150
	D-2448	
Loss on Ignition at 600°C [%]	ASTM	10.0% Max.
	D-6280 (A3)	
Oil Absorption [lbs/100 lbs]	ASTM	17 - 30
[kg/100kg]	D-281	17 - 30
Apparent Bulk Density,		60 - 95
Tapped [g/100 cm ³]		
Fineness of Grind [Hegman	ASTM	6.0 Min.
Value]	D-1210	
Mean Particle Size [microns]	Malvern	8.9
	Mastersizer	

These are typical values and do not represent specifications.

Suggested Applications		
Short and Medium Oil Alkyds		
Long Oil Alkyds		
High Solids Alkyds		
Epoxies – Solvent and Water		
High Solids Epoxies		
Polyurethanes 1K and 2K		
Alkyd Emulsions		
Epoxy Dispersions		
Acrylics and Modified Acrylics		
Hybrids		
Baking Enamels		
Water Reducible Alkyds		

Performance in other coating systems has not been fully evaluated.

The information made herein is based upon our research and the research of others, and is believed to be accurate. No guarantee of accuracy is made and the product discussed is sold without warrant, expressed or implied and upon the condition the purchaser shall make their own tests to determine the suitability of such product for their particular purposes.



07/21/2020

www.wpcamerica.com