



# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY\*

**Product name:** PARALOID™ WR-97 Resin

**Issue Date:** 08/29/2018

**Print Date:** 01/12/2019

THE DOW CHEMICAL COMPANY\* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

**Product name:** PARALOID™ WR-97 Resin

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Coatings product

**COMPANY IDENTIFICATION**

THE DOW CHEMICAL COMPANY\*  
Agent for Rohm and Haas Chemicals LLC  
400 ARCOLA ROAD  
COLLEGEVILLE PA 19426-2914  
UNITED STATES

**Customer Information Number:**

800-258-2436  
SDSQuestion@dow.com

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 1 800 424 9300

**Local Emergency Contact:** 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

**Hazard classification**

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 2

Eye irritation - Category 2A

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

**Label elements**

**Hazard pictograms**



Signal word: **DANGER!**

#### Hazards

Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.

#### Precautionary statements

##### Prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ eye protection/ face protection.  
Use personal protective equipment as required.

##### Response

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

##### Storage

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

##### Disposal

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

No data available

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Chemical nature:** Polymers, solvent based

This product is a mixture.

Component	CASRN	Concentration
-----------	-------	---------------

Acrylic copolymer(s)	Not Hazardous	>= 69.0 - 71.0 %
Isopropanol	67-63-0	20.0 - 30.0 %
Ethylene glycol monobutyl ether	111-76-2	1.0 - 5.0 %
Individual residual monomers	Not Required	<= 9,500.0 PPM
Toluene	108-88-3	< 1.0 %

---

## 4. FIRST AID MEASURES

---

### Description of first aid measures

**Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped. In case of shortness of breath, give oxygen. Call a physician immediately.

**Skin contact:** Wash off with soap and plenty of water. If symptoms persist, call a physician. Remove contaminated clothing. Wash contaminated clothing before re-use. Do not take clothing home to be laundered.

**Eye contact:** Rinse immediately with plenty of water for at least 15 minutes. Get prompt medical attention.

**Ingestion:** Drink 1 or 2 glasses of water. Get prompt medical attention. If vomiting occurs spontaneously, keep airway clear. Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Supportive care is required after significant isopropyl alcohol ingestion. The CNS and CVS must be evaluated. In acute severe exposures to ethylene glycol monobutyl ether, a complete blood count with differential should be performed to examine for reticulocytosis, granulocytosis, leukocytosis, and erythropenia. Severe metabolic acidosis and pulmonary hemorrhage may occur in massive overexposure.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Unsuitable extinguishing media:** No data available

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** No data available

**Unusual Fire and Explosion Hazards:** Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

**Advice for firefighters**

**Fire Fighting Procedures:** EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

**Environmental precautions:** WARNING: KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

**Methods and materials for containment and cleaning up:** Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Vapors can be evolved when material is heated during processing operations. See SECTION 8, Exposure Controls/Personal Protection, for types of ventilation required. Use non-sparking tools and grounding cables when transferring. Wash after handling and shower at end of work period. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

**Conditions for safe storage:** Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steampipes, radiators), from sources of ignition and from reactive materials. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Store out of direct sunlight in a cool place. Keep containers tightly closed in a cool, well-ventilated place. Avoid all ignition sources. Ground all metal containers during storage and handling.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Isopropanol	ACGIH	TWA	200 ppm
	ACGIH	STEL	400 ppm
Ethylene glycol monobutyl ether	OSHA Z-1	TWA	980 mg/m <sup>3</sup> 400 ppm
	ACGIH	TWA	20 ppm
Toluene	OSHA Z-1	TWA	240 mg/m <sup>3</sup> 50 ppm
	OSHA Z-1	TWA	SKIN
	ACGIH	TWA	20 ppm
	OSHA Z-2	TWA	200 ppm
	OSHA Z-2	CEIL	300 ppm
	OSHA Z-2	Peak	500 ppm

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
Ethylene glycol monobutyl ether	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Exposure controls**

**Engineering controls:** Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**Individual protection measures**

**Eye/face protection:** Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

**Skin protection**

**Hand protection:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation.

(Gloves of other chemically resistant materials may not provide adequate protection):  
Nitrile rubber butyl-rubber Solvent-resistant gloves  
Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

**Other protection:** Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact. Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

**Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Up to 1000 ppm organic vapor: Wear a properly fitted NIOSH approved (or equivalent) full-facepiece, air-purifying respirator, OR full facepiece, airline respirator in the pressure demand mode. Above 1000 ppm organic vapor or Unknown: Wear a properly fitted NIOSH approved (or equivalent) self-contained breathing apparatus in the pressure demand mode, OR full-facepiece, airline respirator in the pressure demand mode with emergency escape provision.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance**

<b>Physical state</b>	liquid
<b>Color</b>	clear
<b>Odor</b>	Pungent, sweet odor
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting point/range</b>	-40.00 °C ( -40.00 °F) Initial
<b>Freezing point</b>	No data available
<b>Boiling point (760 mmHg)</b>	82.00 °C ( 179.60 °F) Initial
<b>Flash point</b>	<b>closed cup</b> 17.00 °C ( 62.60 °F) <i>PENSKY MARTENS</i> <i>CLOSED CUP</i>
<b>Evaporation Rate (Butyl Acetate = 1)</b>	>1.00

<b>Flammability (solid, gas)</b>	Not Applicable
<b>Lower explosion limit</b>	1.00 % vol estimated
<b>Upper explosion limit</b>	12.00 % vol estimated
<b>Vapor Pressure</b>	30.0000000 mmHg at 20.00 °C (68.00 °F) estimated
<b>Relative Vapor Density (air = 1)</b>	>1.0000
<b>Relative Density (water = 1)</b>	1.0100
<b>Water solubility</b>	Dilutable
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition temperature</b>	244.00 °C (471.20 °F) estimated
<b>Decomposition temperature</b>	No data available
<b>Dynamic Viscosity</b>	10,000.000 - 17,500.000 mPa.s
<b>Kinematic Viscosity</b>	No data available
<b>Explosive properties</b>	No data available
<b>Oxidizing properties</b>	No data available
<b>Molecular weight</b>	No data available
<b>Percent volatility</b>	28.00 - 32.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** No data available

**Possibility of hazardous reactions:** This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces).  
Product will not undergo polymerization.

**Conditions to avoid:** No data available

**Incompatible materials:** Avoid contact with the following: Strong oxidizing agents Strong acids and strong bases

**Hazardous decomposition products:** There are no known hazardous decomposition products for this material.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### Acute toxicity

#### Acute oral toxicity

Product test data not available. Refer to component data.

**Acute dermal toxicity**

Product test data not available. Refer to component data.

**Acute inhalation toxicity**

Product test data not available. Refer to component data.

**Skin corrosion/irritation**

Product test data not available. Refer to component data.

**Serious eye damage/eye irritation**

Product test data not available. Refer to component data.

**Sensitization**

Product test data not available. Refer to component data.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available. Refer to component data.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available. Refer to component data.

**Carcinogenicity**

Product test data not available. Refer to component data.

**Teratogenicity**

Product test data not available. Refer to component data.

**Reproductive toxicity**

Product test data not available. Refer to component data.

**Mutagenicity**

Product test data not available. Refer to component data.

**Aspiration Hazard**

Product test data not available. Refer to component data.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**Isopropanol**

**Acute oral toxicity**

May cause central nervous system depression. Signs and symptoms of excessive exposure may include: Facial flushing. Low blood pressure. Irregular heartbeats. May cause nausea and vomiting.

LD50, Rat, 5,840 mg/kg OECD 401 or equivalent

**Acute dermal toxicity**

LD50, Rabbit, > 12,800 mg/kg

**Acute inhalation toxicity**

LC50, Rat, male and female, 6 Hour, vapour, > 10000 ppm



**Skin corrosion/irritation**

Prolonged exposure not likely to cause significant skin irritation.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause pain disproportionate to the level of irritation to eye tissues.  
May cause moderate eye irritation.  
May cause moderate corneal injury.  
Vapor may cause eye irritation experienced as mild discomfort and redness.  
Vapor may cause lacrimation (tears).

**Sensitization**

Did not demonstrate the potential for contact allergy in mice.  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.  
Route of Exposure: Ingestion  
Target Organs: Central nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:  
Kidney.  
Liver.  
Kidney effects have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.  
Observations in animals include:  
Lethargy.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

Isopropanol has been toxic to the fetus in laboratory animals at doses toxic to the mother.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, resulting in rapid absorption and injury to other body systems.

**Ethylene glycol monobutyl ether**

**Acute oral toxicity**

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be

significantly less sensitive to hemolysis than those of rodents and rabbits. LD50, Guinea pig, 1,400 mg/kg

LD50, Rat, 1,300 mg/kg

#### **Acute dermal toxicity**

Humans and guinea pigs are resistant to blood effects that are seen for rodents and rabbits. For this reason, the guinea pig data is used as the basis for the acute toxicity classification as it is a better model to assess acute toxicity to humans. LD50, Guinea pig, > 2,000 mg/kg

#### **Acute inhalation toxicity**

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. LC0, Guinea pig, 1 Hour, vapour, > 3.1 mg/l No deaths occurred at this concentration.

#### **Skin corrosion/irritation**

Brief contact may cause slight skin irritation with local redness.  
Repeated exposure may cause irritation, even a burn.  
May cause more severe response on covered skin (under clothing, gloves).

#### **Serious eye damage/eye irritation**

May cause severe eye irritation.  
May cause moderate corneal injury.  
Effects may be slow to heal.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

#### **Sensitization**

Did not cause allergic skin reactions when tested in humans.  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

#### **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

#### **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver.  
Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.

#### **Carcinogenicity**

In long-term animal studies with ethylene glycol butyl ether, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans. If the material is handled in accordance with proper industrial handling procedures, exposures should not pose a carcinogenic risk to man.

#### **Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

#### **Reproductive toxicity**

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

**Mutagenicity**

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**Toluene**

**Acute oral toxicity**

LD50, Rat, 5,580 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, 12,267 mg/kg

**Acute inhalation toxicity**

Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Alcohol consumption and exertion may increase the adverse effects of toluene. LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

**Skin corrosion/irritation**

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:

central nervous system (CNS) effects

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage,

hearing loss, liver and kidney effects and death.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation. Based on Structure-Activity Relationship (SAR), this material is predicted to interfere with fertility or cause birth defects.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Carcinogenicity****Component**

Ethylene glycol monobutyl ether

**List**

ACGIH

**Classification**

A3: Confirmed animal carcinogen with unknown relevance to humans.

---

## 12. ECOLOGICAL INFORMATION

---

*Ecotoxicological information appears in this section when such data is available.*

**General Information**

There is no data available for this product.

**Toxicity****Isopropanol****Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 9,640 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

LC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

NOEC, alga Scenedesmus sp., static test, 7 d, Growth inhibition (cell density reduction), 1,800 mg/l  
ErC50, alga Scenedesmus sp., static test, 72 Hour, Growth rate inhibition, > 1,000 mg/l

**Toxicity to bacteria**

EC50, activated sludge, > 1,000 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 30 mg/l

**Ethylene glycol monobutyl ether**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 1,464 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1,550 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Biomass, 911 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

IC50, Bacteria, Growth inhibition, > 1,000 mg/l

**Chronic toxicity to fish**

NOEC, Danio rerio (zebra fish), semi-static test, 21 d, > 100 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, Other, 100 mg/l

**Toluene**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).  
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

**Acute toxicity to aquatic invertebrates**

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

**Acute toxicity to algae/aquatic plants**

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

IC50, Bacteria, 16 Hour, 29 mg/l

**Chronic toxicity to fish**

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

**Toxicity to soil-dwelling organisms**

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

**Persistence and degradability**

**Isopropanol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 95 %

**Exposure time:** 21 d

**Method:** OECD Test Guideline 301E or Equivalent

10-day Window: Not applicable

**Biodegradation:** 53 %

**Exposure time:** 5 d

**Method:** Other guidelines

**Theoretical Oxygen Demand:** 2.40 mg/mg Estimated.

**Chemical Oxygen Demand:** 2.09 mg/mg Estimated.

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	20 - 72 %
20 d	78 - 86 %

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitization:** OH radicals

**Atmospheric half-life:** 1.472 d

**Method:** Estimated.

**Ethylene glycol monobutyl ether**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

**Biodegradation:** 90.4 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301B or Equivalent

**Theoretical Oxygen Demand:** 2.30 mg/mg

**Chemical Oxygen Demand:** 2.21 mg/g Dichromate

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	5.2 %
10 d	57 %
20 d	72.2 %

**Toluene**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 100 %

**Exposure time:** 14 d

**Method:** OECD Test Guideline 301C or Equivalent

**Theoretical Oxygen Demand:** 3.13 mg/mg Calculated.

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitization:** OH radicals

**Atmospheric half-life:** 2 d

**Method:** Estimated.

**Bioaccumulative potential**

**Isopropanol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.05 Measured

**Ethylene glycol monobutyl ether**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.81 Measured

**Bioconcentration factor (BCF):** 3.2 Fish

**Toluene**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 2.73 Measured

**Bioconcentration factor (BCF):** 13.2 - 90 Fish Measured

**Mobility in soil**

**Isopropanol**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 1.1 Estimated.

**Ethylene glycol monobutyl ether**

Potential for mobility in soil is high (Koc between 50 and 150).

**Partition coefficient (Koc):** 67 Estimated.

**Toluene**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 37 - 178 Estimated.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal methods:** Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

(See 40 CFR 268)

**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. TRANSPORT INFORMATION

---

### DOT

<b>Proper shipping name</b>	Resin solution
<b>UN number</b>	UN 1866
<b>Class</b>	3
<b>Packing group</b>	II

### Classification for SEA transport (IMO-IMDG):

<b>Proper shipping name</b>	RESIN SOLUTION
<b>UN number</b>	UN 1866
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	No
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

### Classification for AIR transport (IATA/ICAO):

<b>Proper shipping name</b>	Resin solution
<b>UN number</b>	UN 1866
<b>Class</b>	3
<b>Packing group</b>	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## 15. REGULATORY INFORMATION

---

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)



**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

**Pennsylvania**

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

**California Prop. 65**

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

**16. OTHER INFORMATION**


---

**Hazard Rating System****HMIS**

Health	Flammability	Physical Hazard
2*	3	0

\* = Chronic Effects (See Hazards Identification)

**Revision**

Identification Number: 10077608 / 1001 / Issue Date: 08/29/2018 / Version: 2.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CEIL	Acceptable ceiling concentration
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
SKIN	Absorbed via skin
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

**Full text of other abbreviations**

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation,

and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY\* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US