Caspol® 1962 Technical Data Sheet



Product Identification

Caspol® 1962 is a 100% solids castor oil based reactive diluent with a blend of primary and secondary hydroxyls with a low molecular weight which gives this triol a high level of reactivity, higher hardness and strength, with a lower elongation than the other Caspol® diols and triols. Caspol® 1962 is a specially modified castor oil polyol which will impart improved coating properties such as chemical resistance, weatherability, flow and application properties.

	<u>Property</u>	<u>Value</u>	
Physical	Acid Value	1	
Properties	Appearance	Pale liquid	
	Color, Gardner	2	
	Density, lbs./gal, 25°C	8.29	
	Equivalent Weight	144	
	Functionality	3	
	Hydroxyl Value	390	
	Moisture, %	0.02	
	Non-Volatile, %	100	
	Specific Gravity, 25°C/25°C	0.996	
	Viscosity, cP @ 25°C	1400	
Applications	 Formulation of 100% solids high performance polyurethane coatings 		
		 Low VOC UV resistant 2-component industrial maintenance coatings and thermosetting OEM coatings 	
	resistance, and chemical	 Property improvements such as; hardness, adhesion, moisture resistance, and chemical resistance in coatings, adhesives, sealants, and elastomeric formulations 	
	 Low VOC force dry and metal 	Low VOC force dry and bake topcoats and primers for plastics and metal	
	 VOC and viscosity reduct 	 VOC and viscosity reduction in coatings, adhesives and sealants 	
	Urethane Intermediates, Polymers		

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA

USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com

Web: www.vertellus.com