



# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY\*

Product name: PARALOID™ B-66 100% Resin

Issue Date: 02/25/2020

Print Date: 02/27/2020

THE DOW CHEMICAL COMPANY\* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

Product name: PARALOID™ B-66 100% Resin

### Recommended use of the chemical and restrictions on use

Identified uses: Coatings product

### COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY\*  
Agent for Rohm and Haas Chemicals LLC  
400 ARCOLA ROAD  
COLLEGEVILLE PA 19426-2914  
UNITED STATES

Customer Information Number:

800-258-2436  
SDSQuestion@dow.com

### EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Combustible dust

Reproductive toxicity - Category 2

### Label elements

Hazard pictograms



Signal word: **WARNING!**

**Hazards**

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Suspected of damaging fertility or the unborn child.

**Precautionary statements****Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response**

IF exposed or concerned: Get medical advice/ attention.

**Storage**

Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

If converted to small particles during further handling, processing, or by other means, may form combustible dust concentrations in air.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Chemical nature:** Acrylic copolymer

This product is a mixture.

Component	CASRN	Concentration
Acrylic polymer(s)	Not hazardous	>= 98.0 - 100.0 %
Individual residual monomers	Not required	< 1.0 %
Toluene	108-88-3	<= 0.7 %
Butyl methacrylate	97-88-1	>= 0.1 - < 1.0 %

---

### 4. FIRST AID MEASURES

---

**Description of first aid measures**

**Inhalation:** Move to fresh air.

**Skin contact:** Wash with water and soap as a precaution. If skin irritation persists, call a physician.

**Eye contact:** Flush eyes with water as a precaution. If eye irritation persists, consult a specialist.

**Ingestion:** Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed:**

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** Treatment should be directed at preventing absorption, administering to symptoms (if they occur), and providing supportive therapy.

---

---

## **5. FIREFIGHTING MEASURES**

---

### **Extinguishing media**

**Suitable extinguishing media:** Use the following extinguishing media when fighting fires involving this material: Carbon dioxide (CO2). Dry chemical. Water spray.

**Unsuitable extinguishing media:** No data available

### **Special hazards arising from the substance or mixture**

**Hazardous combustion products:** No data available

**Unusual Fire and Explosion Hazards:** Material as sold is combustible; burns vigorously with intense heat.

### **Advice for firefighters**

**Fire Fighting Procedures:** Use water spray to cool unopened containers. Remain upwind. Avoid breathing smoke.

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus and protective suit.

---

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

**Environmental precautions:** CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

**Methods and materials for containment and cleaning up:** Floor may be slippery; use care to avoid falling. Eliminate all ignition sources. Ventilate the area. Transfer spilled material to suitable containers for recovery or disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Store in a cool, dry, well ventilated place. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapours/dust. Static charges can accumulate: use bonding and grounding between transfer equipment and receiving containers and for any other operations capable of generating static electricity.

**Conditions for safe storage:** Ground all metal containers during storage and handling. Keep away from heat, sparks, flame, and other sources of ignition.

**Other data:** Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Toluene	ACGIH	TWA	20 ppm
	Further information: visual impair: Visual impairment; female repro: Female reproductive; pregnancy loss: Pregnancy loss; BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section); A4: Not classifiable as a human carcinogen		
	OSHA Z-1		See Further information
	Further information: (2): See Table Z-2		
	OSHA Z-2	TWA	200 ppm
	Further information: Z37.12-1967		
	OSHA Z-2	CEIL	300 ppm
	Further information: Z37.12-1967		
	OSHA Z-2	Peak	500 ppm
	Further information: Z37.12-1967		
Butyl methacrylate	Dow IHG	TWA	50 ppm
	Dow IHG	STEL	75 ppm

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

possible  
after  
exposure  
ceases)

### Exposure controls

**Engineering controls:** Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility.

### Individual protection measures

**Eye/face protection:** Use safety glasses with side shields (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

#### Skin protection

**Hand protection:** Cotton or canvas gloves.

**Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. When dusty conditions are encountered, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	Granular solid
Color	clear
Odor	Acrylic odor
Odor Threshold	No data available
pH	Not Applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	Not applicable
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	May form combustible dust concentrations in air during processing, handling or other means.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor Pressure	Not applicable

<b>Relative Vapor Density (air = 1)</b>	Not applicable
<b>Relative Density (water = 1)</b>	No data available
<b>Water solubility</b>	practically insoluble
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition temperature</b>	393.00 °C (739.40 °F)
<b>Decomposition temperature</b>	No data available
<b>Dynamic Viscosity</b>	Not Applicable
<b>Kinematic Viscosity</b>	No data available
<b>Explosive properties</b>	No data available
<b>Oxidizing properties</b>	No data available
<b>Liquid Density</b>	0.66 g/cm <sup>3</sup> Bulk density
<b>Molecular weight</b>	No data available
<b>Percent volatility</b>	2.00 % maximum

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** No data available

**Possibility of hazardous reactions:** None known.  
Product will not undergo polymerization.  
This material is considered stable.

**Conditions to avoid:** No data available

**Incompatible materials:** There are no known materials which are incompatible with this product.

**Hazardous decomposition products:** Thermal decomposition may yield acrylic monomers..

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### **Information on likely routes of exposure**

Inhalation, Eye contact, Skin contact.

**Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)**

#### **Acute oral toxicity**

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg

**Information for components:**

**Acrylic polymer(s)**

Single dose oral LD50 has not been determined.

**Toluene**

LD50, Rat, 5,580 mg/kg

**Butyl methacrylate**

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 401 No deaths occurred at this concentration.

**Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Based on information for component(s):

LD50, Rabbit, > 3,000 mg/kg

**Information for components:**

**Acrylic polymer(s)**

The dermal LD50 has not been determined.

**Toluene**

LD50, Rabbit, 12,267 mg/kg

**Butyl methacrylate**

LD50, Rabbit, male and female, > 2,000 mg/kg OECD Test Guideline 402

**Acute inhalation toxicity**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

The LC50 has not been determined.

**Toluene**

LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

**Butyl methacrylate**

Prolonged exposure is not expected to cause adverse effects. Vapor may cause irritation of the upper respiratory tract (nose and throat).

LC50, Rat, male and female, 4 Hour, dust/mist, 29 mg/l OECD Test Guideline 403

**Skin corrosion/irritation**

Based on information for component(s):

Brief contact may cause slight skin irritation with local redness.

**Information for components:**

**Acrylic polymer(s)**

Essentially nonirritating to skin.

**Toluene**

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

**Butyl methacrylate**

Brief contact may cause moderate skin irritation with local redness.

**Serious eye damage/eye irritation**

Based on information for component(s):

May cause slight eye irritation.

**Information for components:**

**Acrylic polymer(s)**

Essentially nonirritating to eyes.

**Toluene**

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

**Butyl methacrylate**

May cause slight eye irritation.

Corneal injury is unlikely.

**Sensitization**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

**Toluene**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Butyl methacrylate**

Skin contact may cause an allergic skin reaction.

For respiratory sensitization:



No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

The substance or mixture is not classified as specific target organ toxicant, single exposure.

**Toluene**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

**Butyl methacrylate**

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

**Aspiration Hazard**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No aspiration toxicity classification

**Toluene**

May be fatal if swallowed and enters airways.

**Butyl methacrylate**

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

In animals, effects have been reported on the following organs:

central nervous system (CNS) effects

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage,

hearing loss, liver and kidney effects and death.

**Butyl methacrylate**

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

**Carcinogenicity**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

Did not cause cancer in laboratory animals.

**Butyl methacrylate**

For similar material(s): Did not cause cancer in laboratory animals.

**Teratogenicity**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

**Butyl methacrylate**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

**Reproductive toxicity**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

In animal studies, did not interfere with reproduction.

**Butyl methacrylate**

In animal studies, a similar material has been shown not to interfere with reproduction.

**Mutagenicity**

Product test data not available.

**Information for components:**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

**Butyl methacrylate**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**General Information**

There is no data available for this product.

**Toxicity****Acrylic polymer(s)****Acute toxicity to fish**

No relevant data found.

**Toluene****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

**Acute toxicity to aquatic invertebrates**

LC50, water flea *Ceriodaphnia dubia*, semi-static test, 48 Hour, 3.78 mg/l

**Acute toxicity to algae/aquatic plants**

EbC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

IC50, Bacteria, 16 Hour, 29 mg/l

**Chronic toxicity to fish**

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, *Ceriodaphnia dubia* (water flea), 7 d, number of offspring, 0.74 mg/l

**Toxicity to soil-dwelling organisms**

LC50, *Eisenia fetida* (earthworms), 150 - 280 mg/kg

**Butyl methacrylate****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Pimephales promelas* (fathead minnow), flow-through test, 96 Hour, 11 mg/l, OECD Test Guideline 203

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

LC50, *Oryzias latipes* (Japanese medaka), semi-static test, 96 Hour, 5.57 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, 25.4 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

ErC50, *Pseudokirchneriella subcapitata* (algae), static test, 72 Hour, Growth rate, 31.2 mg/l, OECD Test Guideline 201

NOEC, *Pseudokirchneriella subcapitata* (algae), static test, 72 Hour, Growth rate, 24.8 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

EC10, *Pseudomonas putida*, 18 Hour, 253.6 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, *Daphnia* (water flea), semi-static test, 21 d, 1.1 mg/l

**Persistence and degradability**

**Acrylic polymer(s)**

**Biodegradability:** No relevant data found.

**Toluene**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 100 %

**Exposure time:** 14 d

**Method:** OECD Test Guideline 301C or Equivalent

**Theoretical Oxygen Demand:** 3.13 mg/mg Calculated.

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitization:** OH radicals

**Atmospheric half-life:** 2 d

**Method:** Estimated.

**Butyl methacrylate**

**Biodegradability:** 10-day Window: Not applicable

**Biodegradation:** 88 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301C

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

**Bioaccumulative potential**

**Acrylic polymer(s)**

**Bioaccumulation:** No relevant data found.

**Toluene**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).  
**Partition coefficient: n-octanol/water(log Pow):** 2.73 Measured  
**Bioconcentration factor (BCF):** 13.2 - 90 Fish Measured

**Butyl methacrylate**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).  
**Partition coefficient: n-octanol/water(log Pow):** 3 at 25 °C Estimated.  
**Bioconcentration factor (BCF):** 70 Fish Calculated.

**Mobility in soil**

**Acrylic polymer(s)**

No relevant data found.

**Toluene**

Potential for mobility in soil is very high (Koc between 0 and 50).  
**Partition coefficient (Koc):** 37 - 178 Estimated.

**Butyl methacrylate**

For similar material(s):  
Potential for mobility in soil is low (Koc between 500 and 2000).  
**Partition coefficient (Koc):** 2760 Estimated.

---

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** For disposal, incinerate this material at a facility that complies with local, state, and federal regulations.

**Contaminated packaging:** Empty containers retain product residues. Follow label warnings even after container is emptied. Improper disposal or reuse of this container may be dangerous and illegal. Refer to applicable federal, state and local regulations.

---

---

**14. TRANSPORT INFORMATION**

---

**DOT**

Not regulated for transport

**Classification for SEA transport (IMO-IMDG):**

	Not regulated for transport
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## 15. REGULATORY INFORMATION

---

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Combustible dust  
Reproductive toxicity

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

#### California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

## 16. OTHER INFORMATION

---

### Hazard Rating System

#### HMIS

Health	Flammability	Physical Hazard
1*	1	0

\* = Chronic Effects (See Hazards Identification)

#### Revision

Identification Number: 10004865 / 1001 / Issue Date: 02/25/2020 / Version: 4.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CEIL	Acceptable ceiling concentration
Dow IHG	Dow Industrial Hygiene Guideline
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
STEL	Short term exposure limit
TWA	Time weighted average

**Full text of other abbreviations**

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY\* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and

understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US



## PARALOID™ B-66 100% Resin



### WARNING

**Contains:** Acrylic polymer(s) / Not hazardous; Individual residual monomers / Not required; Toluene / 108-88-3; Butyl methacrylate / 97-88-1

**Hazards:** If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Suspected of damaging fertility or the unborn child. **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** IF exposed or concerned: Get medical advice/ attention. **Storage:** Store locked up. **Disposal:** Dispose of contents/ container to an approved waste disposal plant. **Supplemental information** If converted to small particles during further handling, processing, or by other means, may form combustible dust concentrations in air. Ground all metal containers during storage and handling. Keep away from heat, sparks, flame, and other sources of ignition.

**Refer to the Safety Data Sheet before use.**

### COMPANY IDENTIFICATION

THE DOW CHEMICAL  
COMPANY\*  
Agent for Rohm and Haas  
Chemicals LLC  
400 ARCOLA ROAD  
COLLEGEVILLE PA 19426-2914  
UNITED STATES

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:**  
1 800 424 9300

**Local Emergency Contact:**  
800-424-9300

**Customer Information Number:**  
800-258-2436



©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

### Revision

Identification Number: 10004865 / 1001 / Issue Date:  
02/25/2020 / Version: 4.0