



PRODUCT DATA SHEET

KRYSTOL™ 380

TEST DESCRIPTION	METHOD	SPECIFICATIONS		TYPICAL
		MIN	MAX	
Product Code				KRSTL38
Density, kg/L at 15 °C	ASTM D4052	Report		0.867
Specific Gravity at 25°C	ASTM D4052	0.855	0.880	0.863
Kinematic Viscosity, cSt at 40 °C	ASTM D445	68	90	79
Saybolt Universal Viscosity at 100°F	ASTM D2161	Report		406
Appearance, Visual	LORM 004	Clear & Bright		Clear & Bright
Colour, Saybolt	ASTM D156	+28		>30
Flash point, C O C, ° C (° F)	ASTM D92	240(464)		260 (500)
Pour Point, °C (°F)	ASTM D5950			-15 (5)
Meets UV Absorbance-CFR 178.3620 (b)	ASTM D2269	PASS		PASS

Date Issued: 1/18/2011
Date Reviewed: 1/29/2021

KRYSTOL 380 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA), 21 CFR 178.3620(b) Technical White Mineral Oil
- Certified Kosher Pareve
- Certified Halal
- Expiry Date from Date of Manufacture is 3 years

Petro-Canada Lubricants Inc.

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

lubricants.petro-canada.com